

TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

TB216

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 3,902 lbs.	ROPS/TOPS/FOPS 4 post canopy
Width: 38.6" / 51.2"	LCD gauge panel with multi-functional operator information center
Maximum Dig Depth: 7' 9.1"	Hydraulically retractable track frame
Bucket Digging Force: 4,250 lbs.	Travel alarm
Horsepower / RPM: 15 / 2,400	Two-speed travel with automatic down shift
Travel Speed: 1.4 / 2.6 mph	Control pattern selector valve
Auxiliary Flow: 8.9 gpm	Pilot operated joystick controls with safety lock out
Boom swing: Left 80°/ Right 50°	Cast iron, wrap around counterweight
9" wide rubber tracks	Adjustable suspension seat with 2" retractable seat belt
Long Arm w/ integrated thumb mount	Two-way auxiliary hydraulic circuit routed to the end of the arm
	Variable displacement axial piston main hydraulic pumps
	Adjustable width dozer blade
	Electronic engine monitoring system

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB216	TB216 Equipped with ROPS/TOPS/FOPS canopy, Rubber tracks	\$31,579

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB01608	8" Pin-On Bucket with teeth, 1.1 cu. ft. capacity	\$465
BTB01612	12" Pin-On Bucket with teeth, 1.5 cu. ft. capacity	\$480
BTB01618	18" Pin-On Bucket with teeth, 2.4 cu. ft. capacity	\$557
BTB01624	24" Pin-On Bucket with teeth, 3.2 cu. ft. capacity	\$650
BQC01600	Quick Coupler	\$785
BQC01612	12" Quick Coupler Bucket with teeth, 1.5 cu. ft. capacity	\$480
BQC01618	18" Quick Coupler Bucket with teeth, 2.4 cu. ft. capacity	\$557
BQC01624	24" Quick Coupler Bucket with teeth, 3.2 cu. ft. capacity	\$650
BQC01624D	24" Quick Coupler Ditch Bucket, 3.0 cu. ft. capacity	\$882
BTH216I	INSTALLED Hydraulic thumb (Only compatible w/ 12" or larger Buckets)	\$2,025

FIELD INSTALLED OPTIONS

1914199048	3" Non-retractable seat belt in lieu of standard 2"	\$68
BTH216K	Hydraulic thumb (Only compatible with 12" and larger buckets)	\$1,680