

TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

TB240

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 8,289 lbs.	TOPS/ROPS/FOPS 4 post canopy
Width: 5' 8.5"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 11' 6"	High back adjustable suspension seat
Bucket Digging Force: 9,959 lbs.	Pilot operated joystick control with control pattern change valve
Horsepower / RPM: 35.8 / 2,200	EPA Final Tier 4 compliant engine with DPF and engine monitoring system
Travel Speed: 1.7 / 3.0 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 17.1 gpm	Side by side industrial type radiator and hydraulic oil cooler
Boom Swing: Left 76°/ Right 58°	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continous detent mode
Track width: 13.8"	Safety features include: TOPS/ROPS/FOPS 4 post canopy, travel alarm, retractable seat belt, control lockout, pilot accumulator, mirrors and lights
Two speed travel with automatic shift down	Variable displacement axial piston pump
Reinforced arm w/ Integrated thumb mount	Auto Idle
Heavy duty dozer blade with float	

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB240	TB240 Canopy Equipped with Rubber or Steel Tracks	\$52,760
TB240A (w/Angle Blade)	TB240 Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$55,760

TB240C	TB240 Cab Equipped with Rubber or Steel Tracks TOPS/ROPS/FOPS enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 5.7" color monitor, 12v power outlet	\$60,100
TB240CA (w/ Angle Blade)	TB240 Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$63,100

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB13512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	\$650
BTB13518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	\$675
BTB13524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	\$835
BQC13500	Quick Coupler	\$785
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	\$650
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	\$675
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	\$675
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	\$835
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	\$1,015
BTH135I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	\$1,920

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH135K	Hydraulic thumb (Only compatible with 13" and larger buckets)	\$1,575
1914054391	Bolt on rubber pads (order Qty 2) for TB240 steel track unit	\$1,740



519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

TB260

Compact Excavator

STANDARD EQUIPMENT

<p>Operating Weight: 12,180 lbs. Width: 6' 6.7" Maximum Dig Depth: 12' 9.4" Bucket Digging Force: 12,756 lbs. Horsepower / RPM: 47.6 / 2,400 Travel Speed: 1.7 / 3.0 mph Primary Aux Flow: 27.0 gpm Second Aux Flow: 11.6 gpm Boom Swing: Left 78°/ Right 55° Track Width: 15.7"</p> <p>Two speed travel with automatic shift down Reinforced arm w/ Integrated thumb mount Heavy duty dozer blade with float Auto Idle</p>	<p>TOPS/ROPS/FOPS 4 post canopy Color gauge panel with multi-function operator information center Adjustable high back suspension seat Pilot operated joystick control with control pattern change valve Proportional slide switch control auxiliary hydraulics EPA Final Tier 4 Turbocharged engine with DPF and engine monitoring system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door Side by side radiator and hydraulic cooler Variable Displacement axial piston pump Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch controls Primary auxiliary continuous mode and one-way mode Safety features include: TOPS/ROPS/FOPS 4 post Canopy, travel alarm, retractable seat belt, control lockout, pilot accumulator, mirrors and lights</p>
---	--

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB260	TB260 Equipped with ROPS/TOPS/FOPS canopy, Rubber or Steel Tracks	\$69,716
TB260A (w/Angle Blade)	TB260 Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$72,716
TB260L (w/ Road Liner Tracks)	TB260 Canopy (above Equipped with Road Liner Tracks)	\$74,716
TB260LA (w/ Angle Blade & Road Liner Tracks)	TB260 Canopy (above Equipped with Road Liner Tracks) w/ Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$77,716

TB260C	TB260 Cab Equipped with Rubber or Steel Tracks TOPS/ROPS/FOPS enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 5.7" color monitor, 12v power outlet	\$76,316
TB260CA (w/Angle Blade)	TB260 Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$79,316
TB260CL (w/ Road Liner Tracks)	TB260 Cab (above Equipped with Road Liner Tracks)	\$81,316
TB260CLA (w/ Angle Blade & Road Liner Tracks)	TB260 Cab (above Equipped with Road Liner Tracks) w/ Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$84,316

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB26012	12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity	\$945
BTB26018	18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity	\$1,000
BTB26024	24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity	\$1,080
BTB26036	36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity	\$1,340
BQC26000	Quick Coupler	\$800
BQC14512	12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity	\$945
BQC14518	18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity	\$1,000
BQC14524	24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity	\$1,080
BQC14536	36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity	\$1,340
BQC14536D	36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity	\$1,283
BTH260I	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,070

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH260K	Hydraulic Thumb (Only compatible with 18" and larger buckets)	\$1,722

Prices and specifications
subject to change without notice

P-4
Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
Effective 1 January 2015