



IMPLEMENTS - "COMPACT LOADERS" INDEX

<u>EQUIPMENT DESCRIPTION</u>	<u>LATEST REVISION</u>	<u>PAGE NUMBER</u>
Index	09/22/14	1
Compatibility Chart	09/22/14	2
Loaders	09/22/14	
110TL for WORKMASTER	09/22/14	3
235TLA for Boomer 24	09/22/14	4
250TLA1 for Boomer 33/37	09/22/14	5
260TLA1 for Boomer 41/47 & Boomer 46D/54D	09/22/14	6
250TLA for Boomer 3000 Series	09/22/14	7
270TL for WORKMASTER 45/55	09/22/14	8

Loader Ordering and Pricing Information

Models Used On	Slim Mounts	ROPS	Cab	2wd	4WD	Model	Technical Type	Reference Number	eEquipment Ordering Codes			Loader Arms	Face Plate		Bucket	Loader Mount	Grill Guard	Valve	US List Price
									Package	SAP Package Kit	Bucket		Quick Attach	Pin On					
WORKMASTER 35/40		X			X	110TL	550310513	449324066	PINONB - COMPLETE LOADER KIT WITH PIN ON BUCKET	60IN - 60 INCH BUCKET		X		X	60"	X		X	\$5,462.00
WORKMASTER 35/40		X			X	110TL	550310514	449324076	QKATTB - COMPLETE LOADER KIT WITH QUICK-ATTACH ON BUCKET	60IN - 60 INCH BUCKET		X	X		60"	X		X	\$5,924.00
WORKMASTER 35/40		X			X	110TL	550310515	449324086	QKATTB - COMPLETE LOADER KIT WITH QUICK-ATTACH ON BUCKET	68IN - 68 INCH BUCKET		X	X		68"	X		X	\$6,085.00
Boomer 20/24/25		X			X	235TL	550941102	730892026	FSTPK - FAST PICK	Fast Pick	54 in. Bucket	X		X	54"	X	X	X	\$4,232.00
Boomer 30/35		X			X	240TLA	550941088	730850006	LDRMNT - Loader arms/Mount: Pin-on Bkt	Quick Attach Less Valve	60 in. Bucket	X		X	60"	X			\$5,387.00
Boomer 30/35		X			X	240TLA	550941089	726639152	QALVLV - Quick Attach Less Valve	Quick Attach Less Valve	60 in. Bucket	X	X		60"	X			\$5,848.00
Boomer 30/35		X			X	240TLA	550941090	717275136	QALVLV - Quick Attach Less Valve	Quick Attach Less Valve	68 in. Bucket	X	X		68"	X			\$6,010.00
Boomer 40/50						250TLA	550941076	726582006	LDARMS - Loader Arms Only	Loader Arm Only	NO BUCKET	X							\$4,168.00
Boomer 40/50		X			X	250TLA	550941079	726583056	QALVLV - Quick Attach Less Valve	Quick Attach less Valve	72 in. Bucket	X	X		72"	X			\$6,529.00
Boomer 40/50		X			X	250TLA	550941077	726639416	QALVMT - QUICK ATTACH KIT L VLV AND MNT	Quick Attach less Valve/ mount	72 in. Bucket	X	X		72"				\$5,530.00
Boomer CVT 3040/3045/3050 Serial ZDMB11924 & below (MMV in Cab)			X		X	250TLA	550941093	726585046	CABCVT - Complete LDR QA kit for CVT Cab	Fast Pick	72 in. Bucket	X	X		72"	X		X	\$7,457.00
Boomer CVT 3040/3045/3050 Serial ZDMB11924 & below (MMV in Cab)			X		X	250TLA	550941093	726585046	CABCVT - Complete LDR QA kit for CVT Cab	Fast Pick	72 in. Bucket	X	X		72"	X		X	\$7,457.00
Boomer 33/37	X	X			X	250TLA1	550941103	727099016	THNUPR - Quick Attach Less Valve IV	Fast Pick	68in. Bucket	X	X		68"	X			\$6,283.00
Boomer 41/47	X	X			X	260TLA1	550941104	727100006	THNUPR - Quick Attach Less Valve IV	Fast Pick	72 in. Bucket	X	X		72"	X			\$6,529.00
Boomer CVT 3040/3045/3050 Serial ZDMB11925 & above (MMV under Cab)	X				X	250TLA	550941098	449324026	THNUPR - Quick Attach Less Valve IV	LDR RDY	72 in. Bucket	X	X		72"				\$5,530.00
Boomer CVT 3040/3045/3050 Serial ZDMB11925 & above (MMV under Cab)					X	250TLA	550941095	449324036	THNUPR - Quick Attach Less Valve IV	Fast Pick	72 in. Bucket	X	X		72"	X			\$6,529.00
Boomer 46D Boomer 54D	X	X	X		X	260TLA1 CVT Tier IV	550941107	449324306		LDR RDY	72 in. Bucket	X	X						\$5,530.00
Boomer 46D Boomer 54D	X	X	X		X	260TLA1 CVT Tier IV	550941108	727100016		Fast Pick	72 in. Bucket	X	X		72"	X			\$6,529.00
WORKMASTER 45/55		X		X		270TL	550310489	726639005	LDARMS-ONLY THE LOADER ARMS	FSTPK-FAST PICK	72 in. Bucket	X	X		72"	X		X	\$5,225.00

Current Inv Only

Current Inv Only

Current Inv Only

Current Inv Only

Order Number	Description	US List Price
717746006	BALLAST BOX 500 LB MAX	\$235.00
717747006	BALLAST BOX 1000 LB MAX	\$611.00
717748006	BALLAST BOX 1500 LB MAX	\$813.00
47464281	Conversion Kit for 110TI Loader to fit WORKMASTER 35/40	Order through service parts
LDR10418914	MMV relocation kit - 235TL (Serial YEWLY0117 & below) to fit Boomer 24	Order through service parts



110TL FOR WORKMASTER™ 35 & 40
US PRICE LIST

Standard Equipment

TRACTOR COMPATIBILITY

- WORKMASTER™ 35
- WORKMASTER™ 40

pivot point 2431

- Maximum Rollback (degrees) 23
- Maximum Dump Angle (degrees) 40

SPECIFICATIONS:

Maximum Lift Height (inches) @ Pivot

Pin 100.2

Digging Depth (inches) 2.1

Lift Capacity to maximum lift height (lbs.)

@ bucket pivot point 1262

@ 19.7 in. (500mm) from bucket
pivot point 863

Lift Capacity to 59 in. (1.5m) (lbs.)

@ bucket pivot point 1843

@ 19.7 in. (500mm) from bucket
pivot point 1540

Breakout Force (lbs.)

@ bucket pivot point 3338

@ 19.7 in. (500mm) from bucket

Bucket Capacities

110TL	Struck	Heaped
60" Bucket	.34 cu yd.	.42 cu yd.
68" Bucket	.37 cu yd.	.44 cu yd.
68" HD	.38 cu yd.	.47 cu ya.

*Loader specifications may vary based on tractor model, hydraulic system, tire size, etc.

WARRANTY

New Holland Standard Warranty Applies



235TL FARM LOADER
US PRICE LIST

Standard Equipment

TRACTOR APPLICATION:

Boomer 24

NOTE:

Important Compatibility Information
- 235TL is only compatible with Boomer 24 compact tractors

- To assure proper performance, see Operator's Manual for recommended counterweighting

Loader Specifications:

Lift capacity (bucket pivot pin, max height):

1034 lbs / 470 kg

Lift capacity (500 mm forward, max height):

704 lbs / 320 kg

Lift capacity (bucket pivot pin, 1500 mm height):

1298 lbs / 590 kg

Lift capacity (500 mm forward, 1500 mm height):

968 lbs / 440 kg

Breakout force (bucket pivot pin):

1672 lbs / 760 kg

Breakout force (500 mm forward):

1166 lbs / 530 kg

Bucket roll back force at ground level (500 mm):

1298 lbs / 590 kg

Raising time: 2.4 sec

Lowering time: 1.2 sec

Bucket dumping time: 2.4 sec

Bucket roll back time: 1.2 sec

Max lift height (to bucket pivot pin):
80.7 in / 2050 mm

Max lift height (under level bucket):
75.6 in / 1920 mm

Reach at max lift height:
25.2 in / 640 mm

Max dump angle:
51.0°

Bucket roll back angle:
29.0°

Digging depth:
3.9 in / 100.0 mm

Bucket width:
54.0 in / 1371 mm

Loader specifications may vary based on tractor model, engine speed, hydraulic system, tire type/size, etc.

Bucket Capacities

235TL	Struck	Heaped
54" Bucket	.20 cu yd.	.24 cu yd.

Loader includes Grill Guard

WARRANTY

New Holland Standard Warranty Applies



250TLA1 FARM LOADER
US PRICE LIST

Standard Equipment

Boomer™ 33/37

NOTE:

Important Compatibility Information
-A configured model 250TLA1 is NOT compatible with other model tractors.

To assure proper performance, see Operator's Manual for recommended counterweighting.

Loader Specifications:

Lift capacity (bucket pivot pin, max height):
1822lbs / 826kg
Lift capacity (500 mm forward, max height):
1354 lbs / 614 kg
Lift capacity (bucket pivot pin, 1500 mm height):
2176 lbs / 987 kg
Lift capacity (500 mm forward, 1500 mm height):
1686 lbs / 765kg
Breakout force (bucket pivot pin):
3257 lbs / 1477 kg
Breakout force (500 mm forward):
2444 lbs / 1109 kg
Raising time:
3.8 sec
Lowering time:
2.0 sec
Bucket dumping time:

3.5 sec
Bucket roll back time:
2.2 sec
Max lift height (to bucket pivot pin):
104 in / 2642 mm
Max lift height (under level bucket):
98 in / 2489 mm
Clearance with bucket dumped:
77 in / 1956 mm
Reach at max lift height:
48 in / 1219 mm
Max dump angle:
48 °
Reach with bucket on ground:
78 in / 1981 mm
Bucket roll back angle:
30 °
Digging depth:
6.8 in / 173 mm
Bucket width:
68 in / 1727 mm
Loader specifications may vary based on tractor model, hydraulic system, tire size, etc.

*NOTE: The 250TLA1 do not come configured with a mid mount valve and joystick as these items are now standard on the Boomer™ tractors. If a mid mount valve and joystick are needed, these items must be ordered from parts.
*Couplers are included with loader

WARRANTY
New Holland Standard Warranty Applies



260TLA1 FARM LOADER
US PRICE LIST

Standard Equipment

Boomer™ 41/47
Boomer™ 46D/54D

NOTE:
Important Compatibility Information
-A configured model 260TLA1 is NOT compatible with other model tractors.

To assure proper performance, see Operator's Manual for recommended counterweighting.

Loader Specifications:
Lift capacity (bucket pivot pin, max height):
2371lbs / 1076kg
Lift capacity (500 mm forward, max height):
1849 lbs / 839 kg
Lift capacity (bucket pivot pin, 1500 mm height):
2828 lbs / 1283 kg
Lift capacity (500 mm forward, 1500 mm height):
2256 lbs / 1023kg
Breakout force (bucket pivot pin):
4081 lbs / 1851 kg
Breakout force (500 mm forward):
3191 lbs / 1447 kg
Raising time:
3.8 sec
Lowering time:
2.0 sec
Bucket dumping time:
3.5 sec

Bucket roll back time:
2.2 sec
Max lift height (to bucket pivot pin):
109 in / 2769 mm
Max lift height (under level bucket):
103 in / 2616 mm
Clearance with bucket dumped:
80 in / 2032 mm
Reach at max lift height:
58 in / 1473 mm
Max dump angle:
56 °
Reach with bucket on ground:
86 in / 2184 mm
Bucket roll back angle:
28 °
Digging depth:
6.3 in / 160 mm
Bucket width:
72 in / 1829 mm
Loader specifications may vary based on tractor model, hydraulic system, tire size, etc.

*NOTE: The 260TLA1 do not come configured with a mid mount valve and joystick as these items are now standard on the Boomer™ tractors. If a mid mount valve and joystick are needed, these items must be ordered from parts.
*Couplers are included with loader

WARRANTY
New Holland Standard Warranty Applies



**250TLA FARM LOADER IV
US PRICE LIST**

Standard Equipment

Boomer™ 3040/3045/3050 CAB CVT
Serial # ZDMB11925 and newer ONLY

NOTE:
Important Compatibility Information
-A configured model 250TLA IV is NOT compatible with other model tractors.

To assure proper performance, see Operator's Manual for recommended counterweighting.

Loader Specifications:

Lift capacity (bucket pivot pin, max height):
1822lbs / 826kg

Lift capacity (500 mm forward, max height):
1354 lbs / 614 kg

Lift capacity (bucket pivot pin, 1500 mm height):
2176 lbs / 987 kg

Lift capacity (500 mm forward, 1500 mm height):
1686 lbs / 765kg

Breakout force (bucket pivot pin):
3257 lbs / 1477 kg

Breakout force (500 mm forward):
2444 lbs / 1109 kg

Raising time:
3.8 sec

Lowering time:
2.0 sec

Bucket dumping time:
3.5 sec

Bucket roll back time:
2.2 sec

Max lift height (to bucket pivot pin):
104 in / 2642 mm

Max lift height (under level bucket):
98 in / 2489 mm

Clearance with bucket dumped:
77 in / 1956 mm

Reach at max lift height:
48 in / 1219 mm

Max dump angle:
48 °

Reach with bucket on ground:
78 in / 1981 mm

Bucket roll back angle:
30 °

Digging depth:
6.8 in / 173 mm

Bucket width:
68 in / 1727 mm

Loader specifications may vary based on tractor model, hydraulic system, tire size, etc.

WARRANTY
New Holland Standard Warranty Applies



MODEL 270TL FARM LOADER
US PRICE LIST

(Port of Entry)

Standard Equipment

*Please use Model Breakdown Chart to ensure proper loader choice.

pivot point 3126

TRACTOR COMPATIBILITY:

WorkMaster™ 45/55

Reach @ Maximum Lift (inches) NA
Bucket Rollback (degrees) 34
Bucket Dump Angle (degrees) 57

To assure proper performance, see Operator's Manual for recommended counterweighting.

Loader specifications may vary based on tire size

SPECIFICATIONS:

Maximum Lift Height (inches) @ Pivot Pin 109"

Digging Depth (inches) 4.5

Lift Capacity to maximum lift height (lbs.)

- @ bucket pivot point 2752
- @ 19.7 in. (500mm) from bucket pivot point 1831

Lift Capacity to 59 in. (1.5m) (lbs.)

- @ bucket pivot point 3254
- @ 19.7 in. (500mm) from bucket pivot point 2296

Breakout Force (lbs.)

- @ bucket pivot point 4303
- @ 19.7 in. (500mm) from bucket

This package fully configured "Fast Pick" loader includes:

- Loader Arms
- Quick Attach Face Plate
- 72" Bucket
- Loader Brackets
- loader valve and joystick

270TL	Struck	Heaped
72" Bucket	.46 Cu yd.	.57 Cu yd

WARRANTY

New Holland Standard Warranty Applies