

420F2 BACKHOE LOADER HRC  
LEICESTER, ENGLAND

Ship Weight  
lbs

LIST PRICE  
AT DEALER

Standard Equipment:

THIS LISTING IS A GENERAL DESCRIPTION  
OF A 420F2 BACKHOE LOADER EQUIPPED WITH  
THE LOWEST CHARGE ITEMS.

### **BOOMS, STICKS AND LINKAGES**

14'4" Center pivot excavator style  
backhoe  
Pilot operated joystick hydraulic  
controls with pattern changer valve  
Pilot operated stabilizer controls  
Boom transport lock  
Swing transport lock  
Street pads stabilizer shoes  
Anti-drift hydraulics  
(Boom, Stick and E-Stick)  
Cat Cushion Swing(tm) system  
Bucket level indicator  
Lift cylinder brace  
Return-to-dig (auto bucket positioner)  
Self-leveling loader with single lever  
control  
Transmission neutralizer switch  
Single Tilt Loader

### **POWERTRAIN**

Cat C4.4, 74.5KW (Net 92HP / 69kW)  
Direct Injection Turbo Charged Engine,  
with ACERT technology.  
US EPA Tier4 Final Emissions Compliant  
with Selective Catalytic Reduction(SCR)  
Water separator with service indicator  
Thermal starting aid system  
Eco mode  
A dry-type axial seal air cleaner with  
integral precleaner, automatic dust  
ejection system & filter condition  
indicator  
Hydraulically boosted multi-plate wet  
disk brake with dual pedals & interlock  
Differential lock  
Drive-line parking brake  
High Ambient Cooling Package  
Torque converter  
Transmission--four speed synchro mesh  
with power shuttle & neutral safety  
switch  
Spin-on fuel, engine oil & transmission  
oil filters  
Outboard planetary rear axles  
Open Circuit Breather

### **HYDRAULICS**

Load sensing, variable flow system  
with 43 gpm axial piston pump

420F2 BACKHOE LOADER HRC  
LEICESTER, ENGLAND

Ship Weight  
lbs

LIST PRICE  
AT DEALER

**HYDRAULICS (CONT.)**

6 micron hydraulic filter  
O-ring face seal hydraulic fittings  
Caterpillar XT-3 hose  
Hydraulic oil cooler  
Pilot control shutoff switch  
PPPC, Flow-sharing hydraulic valves  
Hydraulic suction strainer

Tire Valve Stem Protection  
Long Life Coolant -30C (-20F)  
Padlocks (2 on ST, 3 on IT)

**ELECTRICAL**

12 volt electrical start  
150 ampere alternator  
Horn and Backup Alarm  
Hazard flashers/turn signals  
Halogen head lights (4)  
Halogen rear flood lights (4)  
Stop and tail lights  
Audible system fault alarm  
Key start/stop system  
880 CCA maintenance free battery  
Battery disconnect switch  
External/internal power receptacles(12v)  
Diagnostic ports for engine and machine  
Electronic Control Modules  
Remote jump start connector

**OPERATOR ENVIRONMENT**

Lighted gauge group  
Interior rearview mirror  
Rear fenders  
ROPS canopy  
2-inch retractable seat belt  
Tilt steering column  
Steering knob  
Hand and foot throttle  
Automatic Engine Speed Control  
One Touch Low Idle  
Floor mat and Coat Strap  
Lockable storage area  
Air suspension seat

**OTHER STANDARD EQUIPMENT**

Hydrostatic power steering  
Standard Storage Box  
Transport tie-downs  
Ground line fill fuel tank with 44  
gallon capacity  
Ground line fill diesel exhaust fluid  
tank with 5 gallon capacity  
Rubber impact strips on radiator guards  
Bumper  
CD-ROM Parts Manual  
Backhoe Safety Manual  
Operations and Maintenance Manual  
Lockable hood

---

420F2 BACKHOE LOADER HRC  
LEICESTER, ENGLAND

Ship Weight  
lbs

LIST PRICE  
AT DEALER

---

420F2 BACKHOE LOADER HRC  
LEICESTER, ENGLAND

Ship Weight  
lbs

LIST PRICE  
AT DEALER

## ORDERING INSTRUCTIONS

For an explanation of Lane Strategy and ordering instructions please refer to the sales model "GENERAL" posted in the web price list.

The lane you order from will determine capability to order additional attachments and service level you will receive.

## LANE 1 DISTRIBUTION CENTER ARRANGEMENTS

If no reference number is listed, a Lane 1 configuration is not available.

<b>468-5511</b>	<b>420F2 BACKHOE LOADER DCA 1</b> ..... 0 AVAILABLE FROM CLAYTON PRODUCT DISTRIBUTION CENTER Items marked ** are NOT common to all DCAs. 450-8448 **420F2 BHL ST, TIER 4, HRC 337-9696 COUNTERWEIGHT, 1015 LBS 450-8757 ENGINE, 74.5KW,C4.4 ACERT, T4F 450-8730 STICK, EXTENDABLE, 14FT 450-8682 **CANOPY, BASE 433-4804 **SEAT, VINYL 450-8530 **HYDRAULICS, MP, 6FCN/8BNK, ST 450-8606 **PT, 4WD, STD SHIFT 396-6505 **FUEL, COLD WEATHER	<b>\$111,100</b>
<b>468-5512</b>	<b>420F2 BACKHOE LOADER DCA 2</b> ..... 0 AVAILABLE FROM CLAYTON PRODUCT DISTRIBUTION CENTER Items marked ** are NOT common to all DCAs. 450-8448 **420F2 BHL ST, TIER 4, HRC 337-9696 COUNTERWEIGHT, 1015 LBS 450-8757 ENGINE, 74.5KW,C4.4 ACERT, T4F 450-8730 STICK, EXTENDABLE, 14FT 398-2681 **RIDE CONTROL 450-8683 **CAB, DELUXE 450-8715 **AIR CONDITIONER, T4 433-4806 **SEAT, DELUXE FABRIC 450-8530 **HYDRAULICS, MP, 6FCN/8BNK, ST 450-8606 **PT, 4WD, STD SHIFT 398-2882 **COLD WEATHER PACKAGE, 120V HRC	<b>\$124,680</b>

420F2 BACKHOE LOADER HRC LEICESTER, ENGLAND	Ship Weight lbs	LIST PRICE AT DEALER
--	--------------------	-------------------------

<b>468-5513</b>	<b>420F2 BACKHOE LOADER DCA 3</b> ..... 0 AVAILABLE FROM CLAYTON PRODUCT DISTRIBUTION CENTER Items marked ** are NOT common to all DCAs. 450-8450 **420F2 BHL IT, TIER 4, HRC 337-9696 COUNTERWEIGHT, 1015 LBS 450-8757 ENGINE, 74.5KW,C4.4 ACERT, T4F 450-8730 STICK, EXTENDABLE, 14FT 398-2681 **RIDE CONTROL 450-8683 **CAB, DELUXE 450-8715 **AIR CONDITIONER, T4 395-2942 **SEAT, DELUXE FABRIC, HEATED 450-8533 **HYDRAULICS, MP, 6FCN/8BNK, IT 450-8616 **PT, 4WD, AUTOSHIFT 398-2882 **COLD WEATHER PACKAGE, 120V HRC	<b>\$136,770</b>
-----------------	--	------------------

**TO COMPLETE A LANE 1 ORDER  
your order must at least contain.**

- 1: Distribution Center Arrangement (DCA) See choices above.**
- 2: 0P-9001 Lane 1 Order.**
- 3: Selection from each section of the 'LANE 1 MANDATORY' section.**
- 4: Packing references.**

420F2 BACKHOE LOADER HRC  
LEICESTER, ENGLAND

Ship Weight  
lbs

LIST PRICE  
AT DEALER

### LANE 2/ LANE 3 FACTORY ARRANGEMENTS

If no reference number is listed, a Lane 2/ Lane 3 configuration is not available.

Machines ordered in this section will be sourced from the factory.

450-8448	420F2 BHL ST, TIER 4, HRC . . . . . 0 Available for ADSD-N and ADSD-S (Puerto Rico only)	\$85,780
450-8450	420F2 BHL IT, TIER 4, HRC . . . . . 0 Available for ADSD-N and ADSD-S (Puerto Rico only)	\$93,580

**TO COMPLETE A LANE 2/ LANE 3 ORDER  
your order must at least contain.**

- 1: Base Machine Package. See choices above.
- 2: Either 0P-9002 (Lane 2) or 0P-9003 (Lane 3) order reference.
- 3: Selection from each section of the 'LANE2/LANE3 MANDATORY' Section.
- 4: Packing Reference.

Use the reference below when ordering miscellaneous field installed kits.

0G-0556	420F2 MISC MTRL, USA & CNDA . . . . . 0	NC
---------	---	----

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	--------	-----------------	----------------------

**LANE 1 AM-NORTH MANDATORY ATTACHMENTS**

**LANE SELECTION**

0P-9001	LANE 1 ORDER . . . . .	0		NC
	Select this option when ordering from the Distribution Center			

**LOADER BUCKET**

ST machines: Select either 325-5100 or both bucket & cutting edge.  
 IT machines: No selection should be made from this section.  
 If a bucket is required, select 251-1800 & 9R-5320 from the Lane 1 'Finish to Order' section.

P	325-5100	BUCKET, LOADER (NONE) . . . . .	0	NC
		Ship with no loader bucket.		
P	337-7436	BUCKET-MP, 1.3 CYD . . . . .	1,593	\$6,775
		1.35 CYD (1.03CUM) SAE capacity Multi Purpose. Drilled to accept bolt-on teeth or cutting edge (not included). FOR USE WITH: DCA 1 or DCA 2		
P	337-7385	BUCKET-GP, 1.25 CYD . . . . .	965	\$3,167
		1.25 CYD (0.96CUM) SAE capacity General Purpose. Drilled to accept bolt-on teeth or cutting edge (not included). FOR USE WITH: DCA 1 or DCA 2		
P	337-7401	BUCKET-GP, 1.5 CYD . . . . .	1,056	\$4,061
		1.5 CYD (1.15 CUM) SAE capacity General Purpose. Drilled to accept bolt-on teeth or cutting edge (not included). FOR USE WITH: DCA 1 or DCA 2		

**CUTTING EDGES**

Must select if loader bucket required with DCA1 or DCA2.

P	9R-5321	CUTTING EDGE, TWO PIECE . . . . .	154	\$328
		FOR USE IN LANE 3 ONLY Bolt-on reversible cutting edge for the Loader Bucket. FOR USE WITH: Buckets 337-7436 and 337-7385		
P	9R-5320	CUTTING EDGE, TWO PIECE,WIDE . . . . .	154	\$329
		Bolt-on reversible cutting edge for Loader Buckets. FOR USE WITH: Bucket 337-7401		

**TIRES**

Must select.  
 Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice, but we reserve the right to propose alternate tires. Any proposed change will be reviewed with the dealer prior to machine shipment. The machine will ship only with the dealer acceptance of the proposed alternative tire.

P	380-8961	TIRES, 12.5 80/19.5L-24, FS . . . . .	0	\$1,080
		Front: Firestone 12.5/ 80-18, 12 ply, I-3 Super Traction Directional tire with low profile design that provides excellent traction and flotation. Tough sidewall for long wear. Rear: Firestone 19.5L-24, ATU, 12PLY, 20 PITCH Directional tire provides excellent traction and flotation characteristics. Shock-fortified nylon-cord body resists impacts, cuts and punctures. Designed for superior noise and vibration cancellation.		

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	--------	-----------------	----------------------

**LANE 1 AM-NORTH MANDATORY ATTACHMENTS (CONT.)**

**DECAL PACKAGES**

Must select one

P	430-9944	<b>INSTRUCTIONS, ANSI</b> . . . . . 0 This package includes picto decals for use in USA.		NC
P	430-9945	<b>INSTRUCTIONS, ISO</b> . . . . . 0 This package includes picto decals for use outside of USA.		NC

**SEAT BELT**

Select one

L	206-1747	<b>BELT, SEAT, 2" SUSPENSION</b> . . . . . 0 CANNOT BE SELECTED BY: dealers from California, Oregon & British Columbia.		NC
L	206-1748	<b>SEAT BELT, 3" SUSPENSION</b> . . . . . 0 REQUIRED BY: dealers from California, Oregon & British Columbia.		\$106

**STABILIZER PADS**

Must select one

P	9R-1085	<b>STABILIZER PADS, STREET</b> . . . . . 37 Set of two rubber pads which bolt to the standard shoes. For use on prepared surfaces such as asphalt or concrete.		NC
P	9R-6007	<b>STABILIZER PADS, FLIP-OVER</b> . . . . . 85 Flip-over pads for use on asphalt, concrete or soil.		\$327

**BACKHOE BUCKET**

Must select one.

P	175-7877	<b>BUCKET, HOE, (NONE)</b> . . . . . 10 REQUIRED when no backhoe bucket or coupler is installed.		NC
P	219-3387	<b>BUCKET-HD, 24", 6.2 CFT</b> . . . . . 333 Includes 5 tooth tips.	333	\$1,683 \$1,683 NI
P	254-8941	<b>BUCKET-HC SOIL, 24", 8.5 CFT</b> . . . . . 395 INCLUDES: 5 angle-down adapters and soil tooth tips.	395	\$1,818 \$1,818 NI

**INSTRUCTIONS AND OPERATION MANUALS**

Must select

	421-8926	<b>SERIALIZED TECHNICAL MEDIA KIT</b> . . . . . 0 Kit will include instructions and parts CD in the legally required language, based on the shipping address. Any additional media such as a paper parts manual, not included in the kit, can be ordered through the media website. <a href="https://oos.midlandcorp.com/CAT/Default.aspx">https://oos.midlandcorp.com/CAT/Default.aspx</a>		NC
--	----------	--	--	----

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	--------	-----------------	----------------------

**LANE 1 AM-NORTH MANDATORY ATTACHMENTS (CONT.)**

**TRANSPORT PROTECTION**

<b>461-6839</b>	<b>SHIPPING/STORAGE PROTECTION</b> . . . . . 0	<b>\$198 NET</b>
	Provides protective application of Fluid Film TM for protection while shipping and for extended storage periods. This product will need to be power washed with soapy water prior to shipment to the customer. Currently this is only available to, and required by, machines shipping to USA, Canada & South America.	
<b>462-1033</b>	<b>RUST PREVENTATIVE APPLICATOR</b> . . . . . 0	<b>\$105 NET</b>
	Preparation for shipment - Silix applicators required for shipment by sea. Required for all machines for USA, Canada & South America	

**PACKING**

Must select

<b>0P-0210</b>	<b>PACK, DOMESTIC TRUCK</b> . . . . . 0	<b>NC</b>
	Required for all machines for USA, Canada & South America	
<b>0P-3071</b>	<b>FREIGHT SHIP-TO EXCEEDS RADIUS</b> . . . . . 0	<b>NC</b>
	A freight surcharge will be applied for the ship-to locations described below. Any applicable surcharge will be billed separately. Contact your trade lane manager for information. Finning: Locations exceeding 500 km radius of Vancouver and Edmonton Kramer: Locations exceeding 500 km radius of Regina Toromont: Locations exceeding 500 km radius of Toronto and Winnipeg Hewitt: Locations exceeding 500 km radius of Montreal Atlantic: Locations exceeding 500 km radius of Halifax and York NC Machinery: Deliveries to Alaska Hawthorne: Deliveries to Hawaii	

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	--------	-----------------	----------------------

**LANE 1 AM-NORTH OPTIONAL ATTACHMENTS**

*May select additional options (not required).*

P	211-4292	<b>BEACON, MAGNETIC MOUNT</b> . . . . . 0 Must be ordered as 'Not-Installed'.		\$226 NI
P	353-1389	<b>GUARD, STABILIZER</b> . . . . . 0 Guards to protect Stabilizer cylinder rods from damage.		\$815
P	423-7607	<b>PLATE GROUP - BOOM WEAR</b> . . . . . 0 Bolt on guard prevents damage to boom.		\$211
P	337-6851	<b>FENDERS, FRONT</b> . . . . . 0 Set of two fenders with integrated steps.		\$563

**OPTIONAL BUCKET FOR IT MACHINES**

P	251-1800	<b>BUCKET-GP, 1.31 CYD, IT</b> . . . . . 979 1.31 cu. yd. SAE capacity General Purpose. Drilled to accept bolt-on teeth or cutting edge		\$3,610
P	9R-5320	<b>CUTTING EDGE, TWO PIECE, WIDE</b> . . . . . 154 Bolt-on reversible cutting edge for Loader Buckets. REQUIRES: 251-1800 BUCKET, 1.31 CYD GP		\$329

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	--------------------	-------------------------

**LANE SELECTION**

**LANE 2/ LANE 3 FACTORY ARRANGEMENTS**

MACHINES ORDERED FROM THIS SECTION WILL BE SOURCED FROM THE FACTORY

**If no reference number is listed, Lane 2 or Lane 3 configurations are not available.**

<b>0P-9002</b>	<b>LANE 2 ORDER</b> ..... 0 Please select for orders not including the item(s) below.	<b>NC</b>
<b>0P-9003</b>	<b>LANE 3 ORDER</b> ..... 0 Currently only Product Link requires a Lane 3 designation.	<b>NC</b>

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**BOOMS, STICKS AND LINKAGES**

**BACKHOE STICKS**

Select one

L	450-8729	STICK, STANDARD, 14FT .....	0	NC
L	450-8730	STICK, EXTENDABLE, 14FT .....	0	\$4,710
		Provides additional 3'8" (1.13m) of reach		

**POWERTRAIN**

**POWERTRAIN (Gearbox, Axles, Lines)**

Select one

**Two Wheel Drive**

L	450-8600	PT, 2WD, STD SHIFT .....	0	NC
---	----------	--------------------------	---	----

**Four Wheel Drive**

L	450-8606	PT, 4WD, STD SHIFT .....	0	\$9,370
L	450-8616	PT, 4WD, AUTOSHIFT .....	0	\$13,010
L	450-8627	PT, 4WD/2WS, AUTOSHIFT, LTC .....	0	\$15,420
		Autoshift with Lockup Torque Converter		

**ENGINE (Engine, Cooler, Filters, Lines)**

Please select

L	450-8757	ENGINE, 74.5KW,C4.4 ACERT, T4F .....	0	\$6,900
		EPA/ ARB Tier 4 Final Certified engine with aftertreatment. Net Power @ Rated (2200RPM) SAE J1349 92HP (69kW)		

**HYDRAULICS**

**LOADER & BACKHOE HYDRAULICS (inc Valves and Loader Lines)**

Select one

**HYDRAULICS FOR SINGLE TILT MACHINES**

L	450-8525	HYDRAULICS, GP, 5FCN/7BNK, ST .....	0	\$705
		FOR USE WITH: 450-8448 420F2 BHL ST TIER 4 HRC CANNOT BE USED WITH: E-STICK WHEN AUX LINES ARE REQUIRED		
L	450-8527	HYDRAULICS, GP, 6FCN/8BNK, ST .....	0	\$1,430
		FOR USE WITH: 450-8448 420F2 BHL ST TIER 4 HRC		
L	450-8528	HYDRAULICS, MP, 5FCN/7BNK, ST .....	0	\$1,825
		FOR USE WITH: 450-8448 420F2 BHL ST TIER 4 HRC CANNOT BE USED WITH: E-STICK WHEN AUX LINES ARE REQUIRED		
L	450-8530	HYDRAULICS, MP, 6FCN/8BNK, ST .....	0	\$2,550
		FOR USE WITH: 450-8448 420F2 BHL ST TIER 4 HRC		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**HYDRAULICS (CONT.)**

**LOADER & BACKHOE HYDRAULICS (inc Valves and Loader Lines) (Cont.)**

**HYDRAULICS FOR IT (PARALLEL LIFT) MACHINES**

L	450-8531	HYDRAULICS, MP, 5FCN/7BNK, IT . . . . . 0		\$1,980
		FOR USE WITH: 450-8450 420F2 BHL IT TIER 4 HRC		
		CANNOT BE USED WITH: E-STICK WHEN AUX LINES ARE REQUIRED		
L	450-8533	HYDRAULICS, MP, 6FCN/8BNK, IT . . . . . 0		\$2,695
		FOR USE WITH: 450-8450 420F2 BHL IT TIER 4 HRC		

**OPERATOR ENVIRONMENT**

**CAB/ CANOPY**

Select one

L	450-8682	CANOPY, BASE . . . . . 0		NC
		Includes tilt steering column, floor mat, two internal and two external power receptacles and rotating vandal guard.		
L	450-8683	CAB, DELUXE . . . . . 0		\$8,200
		Includes: window defroster, front & rear windshield wiper/washer system, left & right side doors with locks, coat hook, interior rear view mirror, tilt/tele steering column, floor mat, radio-ready headliner, two internal and two external 12v power sockets, auto-up stabilizers, and system indicators for hydraulic filter service and hydraulic temperature warning.		

**SEATING**

Select one

L	433-4804	SEAT, VINYL . . . . . 0		NC
		FOR USE WITH: OPEN CANOPY ONLY		
L	433-4806	SEAT, DELUXE FABRIC . . . . . 0		\$900
		FOR USE WITH: DELUXE ENCLOSED CABS		
L	395-2942	SEAT, DELUXE FABRIC, HEATED . . . . . 0		\$1,400
		FOR USE WITH: DELUXE ENCLOSED CABS		

**SEAT BELT**

Select one

L	206-1747	BELT, SEAT, 2" SUSPENSION . . . . . 0		NC
L	206-1748	SEAT BELT, 3" SUSPENSION . . . . . 0		\$106
		REQUIRED IN: CALIFORNIA		

**ENVIRONMENTAL CONTROL**

SELECT FOR ENCLOSED CABS ONLY

L	450-8714	HEATER, T4 . . . . . 0		NC
		Select if heat only is required.		
		CANNOT BE USED WITH: MACHINES WHICH HAVE AN OPEN CANOPY		
L	450-8715	AIR CONDITIONER, T4 . . . . . 0		\$2,330
		Select if heat and air conditioning is required.		
		CANNOT BE USED WITH: MACHINES WHICH HAVE AN OPEN CANOPY		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**TIRES, RIMS, AND WHEELS**

**TIRES**

Select one

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice, but we reserve the right to propose alternate tires. Any proposed change will be reviewed with the dealer prior to machine shipment. The machine will ship only with the dealer acceptance of the proposed alternative tire.

**TWO WHEEL DRIVE TIRES AVAILABLE FROM FIRESTONE**

P	418-7773	TIRES,12 16.5/19.5L-24, FS,2WD . . . . . 0	\$935
Front: Firestone 12 16.5, 10 ply, Duraforce DT NHS Directional tire for heavy 2WD truck loading. Heavy-duty sidewall and large curb rib for more stability and puncture resistance. Rear: Firestone 19.5L-24, 12ply, All Traction Utility Directional tire provides excellent traction and flotation characteristics. Shock-fortified nylon-cord body resists impacts, cuts and punctures. FOR USE WITH: TWO WHEEL DRIVE POWERTRAINS			

**TWO WHEEL DRIVE TIRES AVAILABLE FROM GOODYEAR**

P	379-2160	TIRES, 11L-16/19.5L-24,GY, 2WD . . . . . 0	\$620
Front: Goodyear 11L-16 12 PR F-3 Laborer Non-Directional tire for lighter 2WD truck loading. Excellent handling and mobility with 5-rib design. Resists tearing and cracking with special tread compound. Rear: Goodyear 19.5L-24 12 PR R4 IT525 Directional tire with solid performance on rock-hard ground. Increased wear and performance on hard surfaces. FOR USE WITH: TWO WHEEL DRIVE POWERTRAINS			

**FOUR WHEEL DRIVE TIRES AVAILABLE FROM FIRESTONE**

P	380-8960	TIRES, 340 80R18/500 70R24, FS . . . . . 0	\$2,310
Front: Firestone 340/80R18 143B, R-4 Radial Duraforce RT Deeper multi-directional tread radial tire for greater pull and wear capability. Radial tires provide improved wear over bias tires and resist cuts, punctures and tears. Rear: Firestone 500/70R24 157B, R-4 Radial Duraforce RT High performance lugs designed for improved traction, pull and wear capability. Rugged radial tire construction provides extra traction, improved wear over biased tires and lower rolling resistance for better efficiency and to reduce operating costs. FOR USE WITH: FOUR WHEEL DRIVE POWERTRAINS			

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**TIRES, RIMS, AND WHEELS (CONT.)**

**FOUR WHEEL DRIVE TIRES AVAILABLE FROM FIRESTONE (Cont.)**

P	282-3855	<b>TIRES, 12.5 80-18/21L-24, FS</b> ..... 0 Front: Firestone 12.5/80-18 NHS (12ply) I-3 Super Traction Loader. Directional tire with low profile design that provides excellent traction and flotation. Tough sidewall for long wear. Rear: Firestone 21L-24 (16ply) R4 ATU (All Traction Utility) Directional tire provides excellent traction and flotation characteristics. Shock-fortified nylon-cord body resists impacts, cuts and punctures. Adds one inch of rear height with improved rear flotation. FOR USE WITH: FOUR WHEEL DRIVE POWERTRAINS	0	\$2,180
P	380-8962	<b>TIRES, 340 80R18/19.5L-24, FS</b> ..... 0 Front: Firestone 340/80R18 143B, R-4 Radial Duraforce RT Deeper multi-directional tread radial tire for greater pull and wear capability. Radial tires provide improved wear over bias tires and resist cuts, punctures and tears. Rear: Firestone 19.5L-24, 12ply, All Traction Utility Directional tire provides excellent traction and flotation characteristics. Shock-fortified nylon-cord body resists impacts, cuts and punctures. FOR USE WITH: FOUR WHEEL DRIVE POWERTRAINS	0	\$1,630
P	380-8961	<b>TIRES, 12.5 80/19.5L-24, FS</b> ..... 0 Front: Firestone 12.5 80-18, 12 ply, I-3 Super Traction Directional tire with low profile design that provides excellent traction and flotation. Tough sidewall for long wear. Rear: Firestone 19.5L-24, ATU, 12PLY, 20 PITCH Directional tire provides excellent traction and flotation characteristics. Shock-fortified nylon-cord body resists impacts, cuts and punctures. Designed for superior noise and vibration cancellation. FOR USE WITH: FOUR WHEEL DRIVE POWERTRAINS	0	\$1,080

**FOUR WHEEL DRIVE TIRES AVAILABLE FROM GOODYEAR**

P	379-2161	<b>TIRES, 12.5 80/19.5L-24, GY</b> ..... 0 Front: Goodyear 12.5 80-1810 PR I-3 Sure Grip Lug Directional tire for good traction and long wear, provided by wide, sturdy overlapping lugs. Rear: Goodyear 19.5L-24 12 PR R4 IT525 Directional tire with solid performance on rock-hard ground. Increased wear and performance on hard surfaces.	0	\$1,450
---	----------	---	---	---------

**FOUR WHEEL DRIVE TIRES AVAILABLE FROM MICHELIN**

P	320-2384	<b>TIRES, 340 80R18/500 70R24, MX</b> ..... 0 Front: Michelin 340/80R18 XMCL 142A8 Directional tire designed to deliver high load capacity, smooth wear and long life with superb grip in all types of conditions. Rear: Michelin 500/70R24 XMCL 157A8 Directional tire designed for outstanding damage resistance,oth extremely long tire life, and high load capacity.of conditions. FOR USE WITH: FOUR WHEEL DRIVE POWERTRAINS	0	\$2,730
---	----------	--	---	---------

USE	REF NO.	<b>LANE 2 / 3 MANDATORY</b>	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------------------	--------------------	-------------------------

**TIRES, RIMS, AND WHEELS (CONT.)**

**FOUR WHEEL DRIVE TIRES FROM MULTIPLE SOURCES**

P	320-2385	<b>TIRES,340 80R18/500/70-24 MI</b> ..... 0 Front: Michelin 340/80R18. Directional tire designed to deliver high load capacity, smooth wear and long life with superb grip in all types of conditions. Rear: Michelin 500/70-24 Power CL 164A8 Directional tire provides excellent traction and flotation characteristics. Shock-fortified nylon-cord body resists impacts, cuts and punctures. Combines benefits of radial front with stability of rear bias. FOR USE WITH: FOUR WHEEL DRIVE POWERTRAINS	\$1,715
---	----------	--	---------

**OTHER ATTACHMENTS**

**COUNTERWEIGHT**

Select one

When selecting counterweights for IT machines, refer to recommendations for the lightest loader attachments to be used.

MINIMUM RECOMMENDED COUNTERWEIGHT

	RECOMMENDED WEIGHT
420F2 ST 2WD Std Stick GP Bucket	530lb
420F2 ST 4WD Std Stick GP Bucket	530lb
420F2 ST 2WD Std Stick MP Bucket	no cwt
420F2 ST 4WD Std Stick MP Bucket	no cwt
420F2 ST 2WD E-Stick GP Bucket	1015lb
420F2 ST 4WD E-Stick GP Bucket	1015lb
420F2 ST 2WD E-Stick MP Bucket	530lb
420F2 ST 4WD E-Stick MP Bucket	530lb
-----	
420F2 IT 2WD Std Stick GP Bucket	no cwt
420F2 IT 4WD Std Stick GP Bucket	no cwt
420F2 IT 2WD Std Stick MP Bucket	no cwt
420F2 IT 4WD Std Stick MP Bucket	no cwt
420F2 IT 2WD Std Stk,Carriage,Fk	no cwt
420F2 IT 4WD Std Stk,Carriage,Fk	no cwt
420F2 IT 2WD Std Stk,Material Ar	no cwt
420F2 IT 4WD Std Stk,Material Ar	no cwt
420F2 IT 2WD E-Stick GP Bucket	530lb
420F2 IT 4WD E-Stick GP Bucket	530lb
420F2 IT 2WD E-Stick MP Bucket	no cwt
420F2 IT 4WD E-Stick MP Bucket	no cwt
420F2 IT 2WD E-Stk,Carriage,Fk	530lb
420F2 IT AWD E-Stk,Carriage,Fk	530lb
420F2 IT 2WD E-Stk,Material Arm	530lb
420F2 IT AWD E-Stk,Material Arm	530lb

P	337-9693	COUNTERWEIGHT, NONE	0	NC
P	337-9694	COUNTERWEIGHT, 255 LBS	0	\$660

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**OTHER ATTACHMENTS (CONT.)**

**COUNTERWEIGHT (Cont.)**

P	337-9695	COUNTERWEIGHT, 530 LBS	0	\$865
P	337-9696	COUNTERWEIGHT, 1015 LBS	0	\$1,725

**Stabilizer Pads and Accessories**

Select one

P	9R-1085	STABILIZER PADS, STREET Set of two rubber pads which bolt to the standard shoes. For use on prepared surfaces such as asphalt or concrete.	37	NC
P	9R-6007	STABILIZER PADS, FLIP-OVER Flip-over pads for use on asphalt, concrete or soil.	85	\$327

**BUCKETS**

**LOADER BUCKETS**

(Must Select One if ordering a ST machine. For IT Work Tools refer to the Optional Attachment section).

P	325-5100	BUCKET, LOADER (NONE) Ship with no loader bucket.	0	NC
P	337-7385	BUCKET-GP, 1.25 CYD 1.25 CYD (0.96CUM) SAE capacity General Purpose. Drilled to accept bolt-on teeth or cutting edge (not included).	965	\$3,167
P	337-7388	BUCKET-GP, 1.4 CYD 1.45 CYD (1.1 CUM) SAE capacity General Purpose. Drilled to accept bolt-on teeth or cutting edge (not included).	1,012	\$3,351
P	337-7401	BUCKET-GP, 1.5 CYD 1.5 CYD (1.15 CUM) SAE capacity General Purpose. Drilled to accept bolt-on teeth or cutting edge (not included).	1,056	\$4,061
P	337-7436	BUCKET-MP, 1.3 CYD 1.35 CYD (1.03CUM) SAE capacity Multi Purpose. Drilled to accept bolt-on teeth or cutting edge (not included). REQUIRES: MP HYDRAULICS	1,593	\$6,775
P	337-7442	BUCKET-MP, 1.4 CYD 1.45 CYD (1.1 CUM) SAE capacity Multi Purpose. Drilled to accept bolt-on teeth or cutting edge (not included). REQUIRES: MP HYDRAULICS	1,655	\$7,278

**CUTTING EDGE/TEETH**

(May select when ordering a bucket)

P	9R-5320	CUTTING EDGE, TWO PIECE,WIDE Bolt-on reversible cutting edge for the Loader Bucket. FOR USE WITH: 337-7401 BUCKET-GP, 1.5 CYD or 337-7442 BUCKET-MP, 1.4 CYD or 337-7396 BUCKET-GP, 1.3 CYD or 337-7445 BUCKET-MP, 1.4 CYD, FORKS CANNOT BE USED WITH: 9R-5866 TEETH	154	\$329
---	---------	--	-----	-------

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**BUCKETS (CONT.)**

**CUTTING EDGE/TEETH (Cont.)**

P	9R-5321	<b>CUTTING EDGE, TWO PIECE</b> ..... 154 Bolt-on reversible cutting edge for the Loader Bucket. FOR USE WITH: 337-7385 BUCKET-GP, 1.25 CYD or 337-7388 BUCKET-GP, 1.4 CYD or 337-7436 BUCKET-MP, 1.3 CYD or 337-7439 BUCKET-MP, 1.3 CYD, FORKS CANNOT BE USED WITH: 9R-5866 TEETH		\$328
P	9R-5866	<b>TEETH</b> ..... 61 Includes eight bolt-on Uniteeth and hardware. FOR USE WITH: ALL GP & MP LOADER BUCKETS CANNOT BE USED WITH: 9R5320 CUTTING EDGE, TWO PIECE,WIDE or 9R5321 CUTTING EDGE, TWO PIECE		\$385

**BACKHOE BUCKETS**

Select one

Additional buckets may be ordered as not-installed from the Lane2/ Lane3 Optional section.

P	175-7877	<b>BUCKET, HOE, (NONE)</b> ..... 10 REQUIRED when no backhoe bucket or coupler is installed.		NC
P	219-3387	<b>BUCKET-HD, 24", 6.2 CFT</b> ..... 333 Includes 5 tooth tips.	333	\$1,683 \$1,683 NI
P	254-8941	<b>BUCKET-HC SOIL, 24", 8.5 CFT</b> ..... 395 Includes 5 angle-down adapters and soil tooth tips.		\$1,818
P	219-3396	<b>BUCKET-HD ROCK, 24", 7.0 CFT</b> ..... 381 Includes 5 tooth tips.		\$1,854
P	219-3381	<b>BUCKET-SD, 24" 6.2 CFT</b> ..... 291 Includes 5 tooth tips.		\$1,308
P	247-1950	<b>BUCKET-HD, 24", 7.3 CFT PL</b> ..... 370 This Pin Lock bucket includes 5 tooth tips. FOR USE WITH: 222-7379 COUPLER, PIN LOCK		\$1,810

**INSTRUCTIONS**

**DECAL PACKAGES**

Select one

P	430-9944	<b>INSTRUCTIONS, ANSI</b> ..... 0 This package includes picto decals for use in USA.		NC
---	----------	---	--	----

**INSTRUCTIONS AND OPERATION MANUALS**

Must select

	421-8926	<b>SERIALIZED TECHNICAL MEDIA KIT</b> ..... 0 Kit will include instructions and parts CD in the legally required language, based on the shipping address. Any additional media such as a paper parts manual, not included in the kit, can be ordered through the media website. <a href="https://oos.midlandcorp.com/CAT/Default.aspx">https://oos.midlandcorp.com/CAT/Default.aspx</a>		NC
--	----------	--	--	----

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**NOTE**

**LANE 2 / LANE 3 OPTIONAL SELECTIONS**

All items may be ordered as Lane 2 unless specifically designated 'FOR USE IN LANE 3 ONLY'.

**HYDRAULICS**

***RIDE CONTROL***

L	398-2681	<b>RIDE CONTROL</b> . . . . . 0	\$1,455
		Improves ride during travel by providing a suspension system in the loader lift arm circuit. Recommended in applications where improved material retention or ride is desired.	

***HYDRAULIC QUICK DISCONNECT***

P	456-3390	<b>COUPLING,QD,THREADED WITH CAPS</b> . . . . . 4	\$363 NI
		This includes one additional male and female threaded flat face, connect under pressure, quick disconnect coupling & protective caps. Compatible with all backhoe work tools. MUST BE ORDERED AS NOT-INSTALLED.	

***BACKHOE HYDRAULICS***

L	398-2852	<b>LINES, COMBINED AUX, STD STICK</b> . . . . . 0	\$3,415
		FOR USE WITH: 450-8729 STICK, STANDARD, 14FT and 5 or 6 FUNCTION HYDRAULICS	
L	398-2853	<b>LINES, COMBINED AUX, E-STICK</b> . . . . . 0	\$3,415
		FOR USE WITH: 450-8730 STICK, EXTENDABLE, 14FT and 6 FUNCTION HYDRAULICS	

**ELECTRICAL**

***MAGNETIC BEACON***

P	211-4292	<b>BEACON, MAGNETIC MOUNT</b> . . . . . 0	\$226 NI
		Must be ordered as 'NOT INSTALLED'	
P	433-0154	<b>BEACON, MAGNETIC MOUNT, STROBE</b> . . . . . 0	\$333 NI
		Must be ordered as 'NOT INSTALLED'.	

***RADIO***

P	387-6597	<b>RADIO &amp; CD PLAYER</b> . . . . . 3	\$590
		Plays music via USB, AUX, Memory Card, CD & FM/AM Radio Removable for security Provides device charging via USB Device controlled from radio CANNOT BE USED WITH: OPEN CANOPY MACHINES	

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**ELECTRICAL (CONT.)**

**RADIO (Cont.)**

P	387-6598	<b>RADIO &amp; CD PLAYER, BLUETOOTH</b> ..... 3 Includes all features from 387-6597 RADIO & CD PLAYER plus: - Bluetooth connectivity - Auto connect & talk (if radio OFF with ignition on) - Built-in microphone CANNOT BE USED WITH: OPEN CANOPY MACHINES		\$695
---	----------	---	--	-------

**RADIO READY CANOPY HEADLINER**

L	398-2875	<b>RADIO READY HEADLINER, CANOPY</b> ..... 3 Canopy headliner to accept a suitable 'all weather' Radio/ CD player (not available from factory) FOR USE WITH: OPEN CANOPIES ONLY		\$486
---	----------	--	--	-------

**FACE FAN**

L	387-6682	<b>FAN, DELUXE CAB</b> ..... 0 FOR USE WITH: DELUXE CABS		\$225
L	454-6610	<b>FAN, STANDARD CAB/ CANOPY</b> ..... 0 FOR USE WITH: CANOPIES		\$225

**SECURITY KEYPAD**

L	387-6570	<b>SECURITY SYSTEM, KEYPAD</b> ..... 0 The keypad unit is a self contained immobiliser system to disable the engine, transmission and other systems at key switch on until a valid pass code is entered on the keypad which unlocks the machine to enable operation.		\$486
---	----------	---	--	-------

**PRODUCT LINK**

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitoring performance of your assets, it helps keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country. contact your Cat marketing representative with any questions.

L	447-0048	<b>PRODUCT LINK, SATELLITE, PL631E</b> ..... 0 FOR USE IN LANE 3 ONLY PL631 uses a satellite network to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. For use in areas with poor or no cellular coverage. REQUIRES: 457-2797 BATTERY, HEAVY DUTY or 398-2882 COLD WEATHER PACKAGE, 120V HRC		\$1,444
L	447-0049	<b>PRODUCT LINK, CELLULAR, PL641I</b> ..... 0 FOR USE IN LANE 3 ONLY PL641 uses GSM and CDMA 3G cellular networks to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data. REQUIRES: 457-2797 BATTERY, HEAVY DUTY or 398-2882 COLD WEATHER PACKAGE, 120V HRC		\$1,208

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**ELECTRICAL (CONT.)**

**HEAVY DUTY BATTERY**

L	457-2797	BATTERY, HEAVY DUTY . . . . . 0 FOR USE IN LANE 3 ONLY INCLUDED IN: COLD WEATHER PACKAGE ONLY AVAILABLE WHEN ORDERING PRODUCT LINK		\$368
---	----------	---	--	-------

**COLD WEATHER ACCESSORIES**

L	398-2882	COLD WEATHER PACKAGE, 120V HRC . . . . . 0 Provides additional battery and engine block heater as well as radiator antifreeze (to -55 celsius), mounting for an ether bottle and low temperature diesel fuel (to -30 celsius). The ether bottle is available seperately from Parts Distribution CANNOT BE USED WITH: HEAVY DUTY BATTERY or COLD WEATHER FUEL		\$760
L	396-6505	FUEL, COLD WEATHER . . . . . 0 Provides low temperature diesel fuel (to -30 celsius). INCLUDED IN: COLD WEATHER PACKAGE		\$68

**GUARDS**

P	423-7607	PLATE GROUP - BOOM WEAR . . . . . 0 Bolt on guard prevents damage to boom.		\$211
P	353-1389	GUARD, STABILIZER . . . . . 0 Guards to protect Stabilizer cylinder rods from damage.		\$815

**OTHER ATTACHMENTS**

**FENDERS**

P	337-6851	FENDERS, FRONT . . . . . 0 Set of two fenders with integrated steps.		\$563
---	----------	---	--	-------

**SERVICE FILTER PACK**

P	399-0118	SERVICE FILTER PACK, T4/C4.4 . . . . . 0 Please order as 'Not-Installed'. This pack includes: Transmission, Engine and Machine hydraulic filters together with fuel water separator filter. NOTE: Only one pack per machine order.		\$99 NI NET
---	----------	---	--	----------------

**WORK TOOLS**

**ATTACHMENTS FOR IT STYLE LOADER ONLY**

P	6W-8832	CARRIAGE, FORK . . . . . 611 Standard carriage. Does not include tines. FOR USE WITH: 450-8450 420F2 BHL IT TIER 4 HRC		\$2,511
P	195-6939	FORK TINE, 2" X 5" X 54" . . . . . 232 One tine only, specify qty of 2 for pair.		\$793

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**WORK TOOLS (CONT.)**

**BACKHOE - WORK TOOLS**

Please note when ordering a coupler:  
318-9902 Bucket Pins are required for EACH ADDITIONAL Bucket.

P	444-7500	<b>COUPLER, PG, MANUAL, DUAL LOCK</b> . . . . . 192 Mechanical quick coupler for backhoe buckets. (Base machine includes one set of pins and hardware to attach one bucket). FOR USE WITH: CAT D, E & F Series Buckets or Work Tools.	192	\$2,026
P	222-7379	<b>COUPLER, PIN LOCK</b> . . . . . 176 Manual coupler for dedicated Pin Lock backhoe work tools. Includes mounting pins and hardware for attaching tools.	176	\$1,631
P	361-1200	<b>COUPLER, PG, HYD, DUAL LOCK</b> . . . . . 192 Hydraulic quick coupler with dual lock for backhoe buckets. REQUIRES: SELECTION FROM HYDRAULIC QUICK COUPLER LINES section below.	192	\$3,967

**HYDRAULIC QUICK COUPLER LINES**

Required if a Hydraulic Quick Coupler has been selected.  
Optional selection on other machines.

P	450-8577	<b>LINES, HYD COUPLER 14FT STD-STK</b> . . . . . 192 Provides hydraulic lines, valve and electrical controller. REQUIRED BY: HYDRAULIC COUPLER, PG, DUAL LOCK and STANDARD STICK	192	\$2,324
P	450-8578	<b>LINES, HYD COUPLER 14FT E-STICK</b> . . . . . 192 Provides hydraulic lines, valve and electrical controller. REQUIRED BY: HYDRAULIC COUPLER, PG, DUAL LOCK and EXTENDABLE STICK	192	\$2,324

**BUCKET PINS**

P	318-9902	<b>PINS, SPARE</b> . . . . . 6 Includes bucket pins and hardware. FOR USE WITH: 444-7500 COUPLER, PG, MANUAL, DUAL LOCK 361-1200 COUPLER, PG, HYD, DUAL LOCK	6	\$175
---	----------	---	---	-------

**BUCKETS**

**LOADER BUCKET FOR IT STYLE LOADER**

P	251-1800	<b>BUCKET-GP, 1.31 CYD, IT</b> . . . . . 979 1.31 cu. yd. SAE capacity General Purpose. Drilled to accept bolt-on teeth or cutting edge REQUIRES: 9R-5320, Cutting Edge, Two Piece, Wide FOR USE WITH: 450-8450 420F2 BHL IT TIER 4 HRC	979	\$3,610
P	251-1794	<b>BUCKET-GP, 1.5 YD3, IT</b> . . . . . 1,030 1.5 cu. yd. SAE capacity General Purpose. Drilled to accept bolt-on teeth or cutting edge (not included). REQUIRES: 9R-5320, Cutting Edge, Two Piece, Wide FOR USE WITH: 450-8450 420F2 BHL IT TIER 4 HRC	1,030	\$4,242
P	216-8840	<b>BUCKET-MP, 1.4 CYD, IT</b> . . . . . 1,612 1.35 cu. yd. SAE capacity Multi Purpose IT. Drilled to accept bolt-on teeth or cutting edge. REQUIRES: 9R-5320, Cutting Edge, Two Piece, Wide FOR USE WITH: 450-8450 420F2 BHL IT TIER 4 HRC	1,612	\$7,482

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**BUCKETS (CONT.)**

**LOADER BUCKET - CUTTING EDGE**

P	9R-5320	CUTTING EDGE, TWO PIECE,WIDE .....154 Bolt-on reversible WIDE cutting edge for Loader Buckets.		\$329
---	---------	---	--	-------

**BACKHOE BUCKETS**

As a result of shipping space limitations, machine shipments will be limited to two 36"pallets including not-installed rear buckets and attachments.

Backhoe Buckets equipped with "Diagonal Retention System" teeth.

W	219-3387	BUCKET-HD, 24", 6.2 CFT ..... 333 Includes 5 tooth tips.		\$1,683 NI
W	254-8941	BUCKET-HC SOIL, 24", 8.5 CFT ..... 395 INCLUDES: 5 angle-down adapters and soil tooth tips.		\$1,818 NI
W	219-3396	BUCKET-HD ROCK, 24", 7.0 CFT ..... 381 INCLUDES: 5 tooth tips		\$1,854 NI
W	219-3381	BUCKET-SD, 24" 6.2 CFT ..... 291 Includes 5 tooth tips.		\$1,308 NI
W	247-1950	BUCKET-HD, 24", 7.3 CFT PL ..... 370 INCLUDES: 5 tooth tips		\$1,810 NI

**FIELD INSTALLED ATTACHMENTS**

**KITS**

Kits cannot be ordered with your machine order.  
Kits can be ordered through CMOPS, but MUST be separate orders from the machine, and MUST include the top level MISC MTRL reference number. To ensure the orders are transferred through Antares to the Parts Distribution System you MUST also select the required Packing reference number.

For USA and Canada, please place your order as follows:

OG-0556 420F2 MISC MTRL  
Kit item number

Kits will not be shipped with your machine, and are not carried in the Waco or Clayton Logistics Nodes.  
Rest of the world may order direct from the plant.  
Please place your order as follows:

OG-0323 420F2 MISC MTRL  
Kit item number  
OG-3280 PACK, MISCL MTRL

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

**RIDE CONTROL**

P	387-6451	<b>KIT, RIDE CONTROL (PILOT/ECM)</b> ..... 0 Provides a suspension system by placing an accumulator in loader lift arm circuit to improve vehicle ride when traveling. For use in roading, load and carry or any other application where bucket spillage or operator ride is a concern. Includes manual on/off switch.		\$1,397 NI
---	----------	---	--	------------

**AUXILIARY, COMBINED FUNCTION HYDRAULIC KITS**

For use with both one-way flow tools (hammers, compactors) and two-way flow tools (augers, thumbs, side tilt couplers). Units equipped with Standard Sticks require 5 function BH Hydraulics and operate using the right thumb controller. Units equipped with Extendible Sticks require 6 Function BH Hydraulics and operate using the left thumb controller. Mounted near the backhoe valve bank in the chassis, a manual ball valve switches between one-way and two-way flow. Estimated shop time: 8 hours to install kit, plus 8 more hours is needed if adding a valve section to the valve bank (converting 4 to 5 Function, or 5 to 6 Function).

P	468-7982	<b>KIT, HYD, COMBINED, 14FT STD STK</b> ..... 0 Provides diverter valve and hydraulic 3/4" lines routed to midpoint of stick for use with one-way or two-way flow work tools. Includes hydraulic quick disconnect couplings. This kit can be used to build 1 way (hammer) lines. See REHS installation instructions. FOR USE WITH: HYDRAULICS, BH, 5 FUNCTION or HYDRAULICS, BH, 6 FUNCTION and STICK, STANDARD		\$3,283 NI
---	----------	--	--	------------

P	468-7981	<b>KIT, HYD, COMBINED, 14FT E-STK</b> ..... 0 Provides diverter valve and hydraulic 3/4" lines routed to midpoint of stick for use with one-way or two-way flow work tools. Includes hydraulic quick disconnect couplings. This kit can be used to build 1 way (hammer) lines. See reference media number REHS installation instructions. FOR USE WITH: E-STICK and HYDRAULICS, BH, 6 FUNCTION		\$3,283 NI
---	----------	--	--	------------

**OTHER KITS**

P	468-7970	<b>KIT, LINES, HYD CPLR 14FT S-STK</b> ..... 0		\$1,700 NI
P	468-7971	<b>KIT, LINES, HYD CPLR 14FT E-STK</b> ..... 0		\$1,700 NI
P	444-7500	<b>COUPLER, PG, MANUAL, DUAL LOCK</b> ..... 192 Mechanical quick coupler for backhoe buckets.		\$2,026 NI
P	361-1200	<b>COUPLER, PG, HYD, DUAL LOCK</b> ..... 192 Hydraulic quick coupler with dual lock for backhoe buckets.		\$3,967 NI

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

**OTHER KITS (Cont.)**

P	387-6458	KIT, GUARD, STABILIZER CYLNDRS . . . . .	0	\$815 NI
P	455-7380	KIT, LOADER, COUPLING QD . . . . . Includes both Male and Female 'Twist to Connect' hydraulic quick disconnect couplings with protective caps.	0	\$363 NI
P	442-9566	KIT, HOE, COUPLING Q-DISCON . . . . . Includes both Male and Female 'Twist to Connect' hydraulic quick disconnect couplings with protective caps.	0	\$363 NI
P	482-1308	KIT, SECURITY KEYPAD . . . . . Provides a kit to add a keypad unit, self contained immobiliser system to disable the engine, transmission and other systems at key switch on until a valid pass code is entered on the keypad which unlocks the machine to enable operation.	0	\$486 NI
P	387-6472	KIT, FENDER, FRONT . . . . . Provides a kit to add a set of 2 Front Fenders to a machine.	0	\$563 NI

**AVAILABLE FROM PARTS DISTRIBUTION**

Please see the WT-BHL price list for other items available from Parts Distribution

**PACKING**

0P-0210	PACK, DOMESTIC TRUCK . . . . .	0	NC
461-6839	SHIPPING/STORAGE PROTECTION . . . . . Provides protective application of Fluid Film TM for protection while shipping and for extended storage periods. This product will need to be power washed with soapy water prior to shipment to the customer. Currently this is only available to, and required by, machines shipping to USA, Canada & South America.	0	\$198 NET
462-1033	RUST PREVENTATIVE APPLICATOR . . . . . Preparation for shipment - Silix applicators required for shipment by sea. Required for all machines for USA, Canada & South America	0	\$105 NET

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**PACKING (CONT.)**

<b>0P-3071</b>	<p><b>FREIGHT SHIP-TO EXCEEDS RADIUS</b> . . . . . 0</p> <p>A freight surcharge will be applied for the ship-to locations described below. Any applicable surcharge will be billed separately. Contact your trade lane manager for further information.</p> <p>Finning: Locations exceeding 500 km radius of Vancouver and Edmonton                  Kramer: Locations exceeding 500 km radius of Regina                  Toromont: Locations exceeding 500 km radius of Toronto, Winnipeg and all deliveries to Newfoundland                  Hewitt: Locations exceeding 500 km radius of Montreal                  Atlantic: Locations exceeding 500 km radius of Halifax and York                  NC Machinery: Deliveries to Alaska                  Hawthorne: Deliveries to Hawaii                  Domestically sourced machines will be shipped to the port of departure.                  Internationally sourced machines will be shipped to the port of entry.</p>	<b>NC</b>
<b>0G-3280</b>	<b>PACK, MISCELLANEOUS MATERIAL</b> . . . . . 0	<b>\$205 NET</b>