

D6K2 TRACK-TYPE TRACTOR
GRENOBLE, FRANCE

Ship Weight
lbs

LIST PRICE
AT PO ENTRY

Standard Equipment:

PRICE LIST INTENDED USAGE

Highly Regulated Countries :
ADSD-N + Puerto Rico + Europe + Turkey +
Israel + French overseas departments and
territories + Japan + ANZ.

POWERTRAIN

Caterpillar C4.4 ACERT diesel engine
turbocharged
EPA Tier 4 Final / EU Stage IV / Japan
2014 (Tier 4 Final) Certified Engine
with Aftertreatment
Aftercooler, Air to Air (ATAAC)
Glowplug starting aid
3000 meter altitude operation capability
w/o de-rating
Hydraulically driven, variable speed fan
Aluminum bar plate cooling system
(radiator, powertrain, aftercooler)
Air cleaner with integrated pre-cleaner,
dust ejector and under hood air intake
Dual path, electronic control, closed-
loop hydrostatic transmission
Electric fuel priming pump
Fuel/water separator
Automatic Traction Control
Programmable/selectable Bi-Directional
shifting
Engine Idle Shutdown
Auto Engine Speed Control

UNDERCARRIAGE

SystemOne or Heavy Duty Undercarriage
Center tread, sprocketed idler with
SystemOne, standard idler with HD
Lifetime lubricated track rollers (8)
and idlers
Carrier rollers (2)
Hydraulic track adjusters
Guards, front/rear guiding
Replaceable sprocket rim segments

HYDRAULICS

Three valve hydraulics
Load sensing hydraulics
Stable Blade control

ELECTRICAL

Horn
Back-up alarm
12V converter, 10A
Diagnostic connector
Batteries, heavy duty, maintenance
free, 900 CCA
Integrated lights (4 front, 2 rear)
100 Amp alternator (24 volt)
24V electric starter

OPERATOR ENVIRONMENT

ROPS/FOPS Cab
Integrated A/C with automatic
temperature control
Seat, air suspended, cloth for cab
Seatbelt, retractable 76 mm (3 inch)
Foot pads, dash
Color graphic 7" display
with gauge for:
engine coolant temperature,
hydraulic oil temperature,
fuel level, diesel exhaust fluid (DEF).
Travel speed limiter, electronic
Engine RPM and gear display
Hour meter, electronic
Engine air cleaner service indicator,
electronic
Water-in-fuel indicator, electronic
Throttle switch, rotary
Eco mode
Controls, seat mounted, fore/aft
adjustment
Armrests, adjustable
Mirror, rearview, inside
Single pedal combining deceleration and
braking functions
Independent forward/reverse speed
settings
Product Link ready GSM or Satellite
Powerport, 12 volt
Coat Hook
Storage compartment
Cup holder
Floor mat, rubber, heavy duty
Intermittent wiper
12V radio ready (plug and play)

FLUIDS

Antifreeze coolant (-37 degrees Celsius/
-34.6 degrees Fahrenheit)
Extended life coolant

D6K2 TRACK-TYPE TRACTOR
GRENOBLE, FRANCE

Ship Weight
lbs

LIST PRICE
AT PO ENTRY

OTHER STANDARD EQUIPMENT

C-frame, variable pitch link, hydraulic
cylinder and lines
Engine enclosures
Hinged radiator louvered grill
Swing-out radiator fan
Front pull device
Rigid drawbar
Vandalism protection
Ecology drains (engine, powertrain and
implement oil, engine coolant)
Scheduled Oil Sampling ports (engine,
powertrain and implement oil)
Heavy duty crankcase guard
Slope indication
CAT Grade Control Slope Assist

INSTRUCTIONS

Warning Decals, ANSI, for machines in
in the USA only

D6K2 TRACK-TYPE TRACTOR
GRENOBLE, FRANCE

Ship Weight
lbs

LIST PRICE
AT PO ENTRY

ORDERING INSTRUCTIONS

Supersedes
US-A D

Caterpillar: Confidential Green

Subject to change without notice
Printed in USA
U. S. DOLLAR CURRENCY

Effective 06OCT2015
D6K2-4F-003

D6K2 TRACK-TYPE TRACTOR
GRENOBLE, FRANCE

Ship Weight
lbs

LIST PRICE
AT PO ENTRY

You must order your machine from Lane 1, Lane 2 or Lane 3.
The Lane you order from will determine capability to order
additional attachments and service level you will receive.

Lane 2 or Lane 3 orders must include selections from the MANDATORY
sections, and may be completed with OPTIONAL features.

For further explanations of Lane Strategy and ordering instructions
please refer to the sales model "General" posted in the web price
list.

C = Custom attachments.
Availability may be longer than PSL LANE 3 for products marked "C",
please contact Order Entry for current availability.

LANE 1 DISTRIBUTION CENTER ARRANGEMENTS
If no reference is listed, no lane 1 configuration is available.

LANE 2/LANE 3 FACTORY ARRANGEMENTS

456-8039	D6K2 XL TRACTOR	11,468	\$207,840
424-5551	D6K2 LGP TRACTOR	11,552	\$218,200
0G-0515	D6K2 MISC MATERIAL GRENOBLE	0	NC

Use this top level reference when ordering miscellaneous
material without ordering a machine.

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT PO ENTRY
-----	---------	-----------------------------	--------------------	---------------------------

LANE SELECTION

YOUR ORDER WILL BE LANE 2 UNLESS YOU SELECT A PACKAGE OR ATTACHMENT LISTED AS LANE 3 ONLY.

Select One

0P-9002	LANE 2 ORDER	0	NC
0P-9003	LANE 3 ORDER	0	NC

REGIONAL PACKAGES

Select One

L	465-0450	REGIONAL PACKAGE ADSD-N 1,221 Includes: Standard engine enclosure Warning Decals, AINSI	NC
----------	-----------------	---	-----------

POWERTRAIN

ENGINE AIR CLEANER

Select One

L	424-9844	AIR CLEANER, STANDARD 0	NC
----------	-----------------	--------------------------------------	-----------

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT PO ENTRY
-----	---------	-----------------------------	--------------------	---------------------------

UNDERCARRIAGE

SystemOne can be used in most of the HD sealed and lubricated applications.
 Center tread idlers now run on the bushings instead of the links, eliminating link scalloping, substantially increasing links life, O&O costs are significantly reduced by elimination of bushing turns and increased components wear life.

Due to the potential increase in undercarriage life resulting from SystemOne, Extreme Service (ES) shoes should be considered for applications that are anticipated to be shoe-life limited in order to match shoe life with link life.

Customers should carefully select between SystemOne and Heavy Duty undercarriage based on expected application.
 For attachment guiding / guarding (for SystemOne and Heavy Duty configurations), see the Track Guiding Guard Arrangements section.

It is recommended the machines use Heavy Duty undercarriage in high debris packing applications.

UNDERCARRIAGE

Select One

L	431-7079	ROLLERFRAME, 8/2 SYSTEMONE 0 Includes: -SystemOne undercarriage with 8 rollers and 2 carriers rollers	NC
L	431-7080	ROLLERFRAME, 8/2 HEAVY DUTY 0 Includes: -Heavy Duty undercarriage with 8 rollers and 2 carriers rollers	\$-5,970

TRACKS (40 Sections)

Select One

Track Pairs, XL, SystemOne

L	390-2809	TRACK, 20", MS, XL 4,295 FOR USE IN LANE 3 ONLY Moderate Service shoes. ONLY FOR USE WITH: XL machines. SystemOne rollerframe Lane 3 only	\$-132
---	----------	--	--------

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT PO ENTRY
-----	---------	----------------------	-----------------	------------------------

UNDERCARRIAGE (CONT.)

Track Pairs, XL, SystemOne (Cont.)

L	390-2810	TRACK, 20", ES, XL Extreme Service shoes. ONLY FOR USE WITH: XL machines. SystemOne rollerframe	4,612	\$790
L	390-2808	TRACK, 22", MS, XL Moderate Service shoes. ONLY FOR USE WITH: XL machines. SystemOne rollerframe	4,497	NC
L	379-3980	TRACK, 22", ES, XL Extreme Service shoes. ONLY FOR USE WITH: XL machines. SystemOne rollerframe	4,863	\$920

Track pairs, XL, Heavy Duty

L	391-3941	TRACK, 20", ES, XL, HD Extreme Service shoes. ONLY FOR USE WITH: XL machines. Heavy Duty rollerframe	0	\$-132
L	379-3982	TRACK, 22", ES, XL, HD FOR USE IN LANE 3 ONLY Extreme Service shoes. ONLY FOR USE WITH: XL machines. Heavy Duty rollerframe Lane 3 only	0	NC

Track pairs, LGP, SystemOne

L	390-2812	TRACK, 30", MS, LGP Moderate Service shoes. ONLY FOR USE WITH: LGP machines. SystemOne rollerframe	5,401	NC
L	379-3981	TRACK, 30", ES, LGP Extreme Service shoes. ONLY FOR USE WITH: LGP machines. SystemOne rollerframe	5,900	\$1,320

Track pairs, LGP, Heavy Duty

L	379-3983	TRACK, 30", ES, LGP, HD Extreme Service shoes. ONLY FOR USE WITH: LGP machines. Heavy Duty rollerframe	5,900	\$1,320
---	----------	---	-------	---------

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT PO ENTRY
-----	---------	----------------------	-----------------	------------------------

UNDERCARRIAGE (CONT.)

Track pairs, LGP, Heavy Duty (Cont.)

L	416-0036	TRACK, 30", SELF CLEAN, LGP FOR USE IN LANE 3 ONLY ONLY FOR USE WITH: LGP machines Heavy Duty rollerframe Lane 3.	5,410	\$8,520
---	----------	---	-------	---------

TRACK GUIDING GUARDS

Select One

Track Guiding guards, 8/2, SystemOne

L	382-6523	GUARD, TRACK GUIDING, CENTER Center guard section ONLY FOR USE WITH: SystemOne rollerframe	88	\$935
L	382-6525	GUARD, TRACK GUIDING, F&R Front and rear guard section ONLY FOR USE WITH: SystemOne rollerframe	0	\$1,680
L	368-9742	GUARD, TRACK GUIDING, FULL 8/2 Full length guard section ONLY FOR USE WITH: SystemOne rollerframe	0	\$2,550

Track Guiding guards, 8/2, Heavy Duty

L	368-9744	GUARD, TRACK GUIDING, CTR Center guard section ONLY FOR USE WITH: Heavy Duty rollerframe	0	\$935
L	382-6524	GUARD, TRACK GUIDING, F&R Front and rear guard section ONLY FOR USE WITH: Heavy Duty rollerframe	0	\$1,680
L	368-9741	GUARD, TRACK GUIDING, FULL 8/2 Full length guard section ONLY FOR USE WITH: Heavy Duty rollerframe	0	\$2,550

No guiding guard

L	234-4747	GUARD, TRACK GUIDING, NONE No track guiding will be provided when selecting this attachment.	0	NC
---	----------	---	---	----

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT PO ENTRY
-----	---------	----------------------	-----------------	------------------------

HYDRAULICS (CONT.)

HYDRAULIC FAN

Select One

L	424-7002	FAN, DEMAND 13 Electronically controlled hydraulic demand fan drive. Automatically adapts cooling to engine heat load. Recommended when the machine is used in cold and hot environments. ONLY FOR USE WITH: Ripper, Drawbar or Counterweight, rear		NC
L	424-7003	FAN, DEMAND, REVERSING 18 Electronically controlled hydraulic demand fan drive. Automatically adapts cooling to engine heat load. Allows to reverse air flow through the radiator. Recommended for applications with a risk of radiator plugging. ONLY FOR USE WITH: Ripper, Drawbar or Counterweight, rear		\$1,700
L	424-7004	FAN, DEMAND, WINCH 13 FOR USE WITH LANE 3 Electronically controlled hydraulic demand fan drive. Automatically adapts cooling to engine heat load. Recommended when the machine is used in cold and hot environments. ONLY FOR USE WITH: Winch		NC
L	424-7005	FAN, DEMAND, REVERSING, WINCH 18 FOR USE WITH LANE 3 Electronically controlled hydraulic demand fan drive. Automatically adapts cooling to engine heat load. Allows to reverse air flow through the radiator. Recommended for applications with a risk of radiator plugging. ONLY FOR USE WITH: Winch		\$1,700

STARTERS, BATTERIES, & ALTERNATORS

STARTERS

Select One

L	465-5604	STARTER, STANDARD 0		NC
L	465-5611	STARTER, LOW TEMPERATURE 0 Recommended with a cold weather package in extremely low application.		\$800

OPERATOR ENVIRONMENT

CAB PACKAGES

Select One

L	422-5372	CAB STANDARD PACKAGE 0 Includes standard cab and air suspension seat.		NC
---	----------	---	--	----

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT PO ENTRY
-----	---------	----------------------	-----------------	------------------------

OPERATOR ENVIRONMENT (CONT.)

CAB PACKAGES (Cont.)

L	493-2899	CAB PACKAGE, HD 0 Includes : -Heavy Duty cab with polycarbonate windows, -Air suspension seat, -Standard joystick control handles, -Wiring camera-ready cab. Recommended with the kit visibility, single camera, available in the optional section of this price list.		\$1,510
L	487-6134	CAB COMFORT PACKAGE 0 Includes : -Standard cab, -Air suspension, heated and ventilated seat, -Heated joystick control handles, -Wiring camera-ready cab. Recommended with the kit visibility, single camera, available in the optional section of this price list.		\$1,960

TECHNOLOGY PRODUCTS

ACCUGRADE CONTROL

ACCUGRADE CONTROL SYSTEM ORDERING

- (1) Ordering **INSTALLATION, ACCUGRADE READY (ARO)** allows the machine to be equipped with an **AccuGrade GNSS (GPS and GLONASS satellite constellations), Laser or UTS Grade Control System Electronics Kit.**
- (2) An **AccuGrade Electronics Kit (GNSS, Laser, or UTS)** must be ordered separately and additional to the machine.
- (3) The purchase of a **AccuGrade Software Enabled Attachment (SEA)** premium configuration is required for those configurations requiring automatic blade control and must be ordered separately and additional to the machine and the **AccuGrade Electronics Kit.**
- (4) **Site infrastructure** is also necessary to operate the **AccuGrade system.** For example, **GNSS systems** require a **GNSS base station.** **Laser systems** require a **laser transmitter.** **UTS** requires a **Universal Total Station.**

Please consult the **ACCUTTT1** price list for ordering instructions for electronics kits, **AccuGrade SEA** and site infrastructure.

Select One

L	488-2587	NO ARO, MECHANICAL PITCH 0		NC
L	488-2588	ARO, MECHANICAL PITCH 0		\$4,890

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT PO ENTRY
-----	---------	-----------------------------	--------------------	---------------------------

TECHNOLOGY PRODUCTS (CONT.)

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country. Please contact your Cat marketing representative with questions.

Select One

L	421-9198	PRODUCT LINK, SATELLITE PL631 9 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. For use in areas with poor or no cellular coverage.	NC
L	421-9199	PRODUCT LINK, CELLULAR PL641 2 Product Link Pro series PL641 uses GSM and CDMA 3G cellular networks to transmit location, utilization and condition information viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data.	NC
L	319-4492	NO PRODUCT LINK 0	NC

FUEL SYSTEMS

TANK FUEL

Select One

L	425-7127	TANK FUEL, STANDARD 0 Standard tank fuel	NC
L	459-1505	TANK FUEL, FF & REFILL READY15 Provides fuel tank with openings for either the fast fill system or the refilling fuel pump. CANNOT BE USED WITH: screen, rear cab, protection packages Winch preparation	\$213

GUARDS

PROTECTION PACKAGES

Select One

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT PO ENTRY
-----	---------	----------------------	-----------------	------------------------

GUARDS (CONT.)

PROTECTION PACKAGES (Cont.)

L	459-1753	PROTECTION PACKAGE, STANDARD 516 Includes: - Guard, fuel tank, standard 4mm-thick steel guard protecting rear of the machine. - Grill radiator, standard - Guard, crankcase, standard		NC
L	459-1755	PROTECTION PACKAGE, FRONT 692 This package is recommended in harsh environments Includes: - Guard, fuel tank, standard 4 mm-thick steel guard protecting rear of the machine. - Grill, radiator, Heavy duty Heavy duty radiator grill. Provides additional protection to the radiator. - Guard, crankcase, standard		\$525
L	459-1756	PROTECTION PACKAGE, HEAVY DUTY 1,045 This package is recommended for severe applications. Includes: - Guard, fuel tank, Heavy duty 10 mm-thick steel guard protecting rear of the machine. - Grill, radiator, Heavy duty Heavy duty radiator grill Provides additional protection to the radiator. - Guard, crankcase, heavy duty Recommended in harsh environments.		\$2,380

OTHER ATTACHMENTS

REAR ATTACHMENTS

Select One

P	487-6096	PACKAGE RIPPER, TEETH STRAIGHT 2,167 0 Includes: - Ripper, D6K, Multi-shank Ripper, hydraulic, parallelogram rear-mounted. When installed on an LGP machine, the ripper is intended for scarifying hard soil only, not for normal ripping applications. - Teeth straight, set of 3 Three straight shank ripper teeth ONLY FOR USE WITH: Ripper ready packages or Dual control packages		\$14,630 \$14,630 NI
---	----------	--	--	-------------------------

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT PO ENTRY
-----	---------	-----------------------------	-----------------	------------------------

OTHER ATTACHMENTS (CONT.)

REAR ATTACHMENTS (Cont.)

P	487-6095	PACKAGE RIPPER, TEETH CURVED	2,167 0	\$14,630 \$14,630 NI
---	----------	---	------------	-------------------------

Includes:
 - Ripper, D6K, Multi-shank
 Ripper, hydraulic, parallelogram rear-mounted.
 When installed on an LGP machine, the ripper is intended for scarifying hard soil only, not for normal ripping applications.
 - Teeth curved, set of 3
 Three curved shank ripper teeth
ONLY FOR USE WITH: Ripper ready packages or Dual control packages

NOTE: Ripper can be ordered INSTALLED or NOT INSTALLED with the machine, or through a MISCELLANEOUS order.

P	295-7680	WINCH PREPARATION	0	\$-296
---	----------	------------------------------------	---	--------

FOR USE WITH LANE 3
 PA50 winch, listed under Field Installed Attachments section, requires this Winch Preparation and Winch ready Hydraulics. PA50 winch to be ordered through a MISCELLANEOUS order. Please refer to Field Installed Attachments section for winch ordering instructions.
REQUIRES: Cab, protection Package (containing rear screen) or Screen
ONLY FOR USE WITH: Winch ready package or Dual control packages
CANNOT BE USED WITH: Tank fuel, fast fill & refill ready

L	246-8384	DRAWBAR	176	NC
---	----------	--------------------------	-----	----

P	340-5429	COUNTERWEIGHT, REAR	1,190 0	\$3,790 \$3,790 NI
---	----------	--------------------------------------	------------	-----------------------

Provides a 540 kg (1190 lbs) rear counterweight (includes a rear drawbar) to reach optimum balance if extra weight is added to the front of the machine and when no ripper or winch is installed. Extra slabs (78 kg / 172 lbs) each are available. Counterweight and slabs can be ordered INSTALLED with the machine, or through a MISCELLANEOUS order.

L	449-5863	NO REAR ATTACHMENT	0	NC
---	----------	-------------------------------------	---	----

This reference must be selected only when the dealer wants to install his own rear attachments at the dealership or in the field. In any case, the machine must be sold to the final customer with an appropriate rear attachment (drawbar, ripper, winch, counterweight) to reach the optimum balance of the complete machine and to keep a safe access to the fuel tank. Orders with this no rear attachment will be accepted by the factory only if the final rear configuration is explained and justified with a note in the MSO. Please check the global configuration of the machine is consistent with the intended rear equipment.

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT PO ENTRY
-----	---------	----------------------	-----------------	------------------------

BLADES

All blades now come AccuGrade Ready
They include mounting brackets for AccuGrade receivers.

Select One

P	348-6300	BLADE, 126" ARO XL 0 Power-Angle-Tilt XL blade with finishing end bits. REQUIRES: OG-3256 PACK-DISMOUNTED OR NI BLADE ONLY FOR USE WITH: XL machines.		\$7,600 NI
P	371-0749	BLADE, 126" FOLDABLE ARO XL 0 Power-Angle-Tilt XL blade with finishing end bits. Blade has one foldable end which can be manually folded toward the front of the machine to fit within the 2.50 meter (8.36 ft) transportation width. ONLY FOR USE WITH: XL machines	0	\$11,420 \$11,420 NI
P	348-6280	BLADE, 145" ARO LGP 0 Power-Angle-Tilt LGP blade with finishing end bits. REQUIRES: OG-3256 PACK-DISMOUNTED OR NI BLADE ONLY FOR USE WITH: LGP machines		\$7,960 NI
P	371-0779	BLADE, 145" FOLDABLE ARO LGP 0 Power-Angle-Tilt LGP Blade with finishing end bits. Blade has one foldable end which can be manually folded toward the front of the machine to fit within the 3.00 meter (9.84 ft) transportation width. ONLY FOR USE WITH: LGP machines	0	\$11,940 \$11,940 NI
P	340-7729	NO BLADE 0 Select this reference when no blade desired with the machine.		NC

FLUIDS

HYDRAULIC OIL

Select One

L	249-3095	HYDRAULIC OIL, STANDARD 161 Standard hydraulic oil, factory filled. For the implement hydraulic system only.		NC
L	249-3097	HYDRAULIC OIL, BIO 0 This hydraulic environmental Ester Synthetic oil is recommended for hydraulic system when environmental compliance is required or desired Factory filled. Applies to the implements and transmission hydraulic systems.		\$1,965

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT PO ENTRY
-----	---------	-----------------------------	--------------------	---------------------------

PACKING

Export Packing

Select One

0G-9236	COMPLETE STORAGE PROTECTION 0	\$224 NET
	<p>Machines have been sprayed with Fluid Film TM. This product is added for corrosion protection while shipping and for extended storage periods. This product will need to be power washed with soapy water prior to shipment to the customer. Cilix AND foam protection on all cylinders are also included in this storage protection procedure. Recommended : Sea and all type or long distance shipment</p>	

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT PO ENTRY
-----	---------	----------------------	-----------------	------------------------

STARTERS, BATTERIES, & ALTERNATORS

COLD WEATHER PACKAGES

L	465-5002	COLD WEATHER, 120V, PACKAGE 2 Recommended in cold ambient temperature environments. Includes: Heater, engine coolant, 120V Ether starting aid		\$235
---	----------	--	--	-------

BREATHER

L	485-7652	ELECTRICAL INSULATED BREATHER 0 FOR USE IN LANE 3 ONLY For operation on ambient climates of -25°C to -40°C, it is recommended that the cold climate pack is fitted. This consists of a heated filter canister and insulated hoses. ONLY FOR USE WITH: Lane 3 only		\$1,840
---	----------	--	--	---------

ELECTRICAL

L	358-3947	BEACON, ROTATING 7 Rotating Beacon. Heavy duty bracket design allows beacon to be retracted to avoid damage during transportation in wooded areas.		\$620
---	----------	--	--	-------

OPERATOR ENVIRONMENT

P	438-8473	KIT VISIBILITY, SINGLE CAMERA 0 The camera system can be used to enhance the operators visibility of his surroundings, or provide a better view of his work tool. The image is included in the main machine display when the machine is placed in reverse gear. This kit visibility can be ordered installed on the machine, or through MISCELLANEOUS orders. ONLY FOR USE WITH: Cab Comfort or Heavy Duty packages.	0	\$500 \$500 NI
---	----------	---	---	-------------------

GUARDS

CAB PROTECTIONS

L	465-0427	CAB, PROTECTION PACKAGE 525 This Package is recommended for forestry and severe applications. Includes : - Sweeps, Cab Bolt-on sweeps. - Screen, Rear Cab Protective screen for rear window. REQUIRED BY : Winch Preparation CANNOT BE USED WITH: Tank, fuel fast fill & refill ready		\$4,410
---	----------	--	--	---------

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT PO ENTRY
-----	---------	----------------------	-----------------	------------------------

GUARDS (CONT.)

CAB PROTECTIONS (Cont.)

L	465-0428	CAB, PROTECTION PACKAGE, HD 791 This Package is recommended for forestry and severe applications. Includes : - Sweeps, Cab Bolt-on sweeps. - Screen, rear Cab Protective screen for rear window. - Guard, lights, rear Protective screen for rear lights. - Screen, side Protective screens for side windows. REQUIRED BY : Winch Preparation CANNOT BE USED WITH: Tank, fuel fast fill & refill ready		\$6,300
L	441-5461	SCREEN, REAR 75 FOR USE WITH LANE 3 ONLY Protective screen for rear window. Recommended for forestry and severe applications. REQUIRED BY Winch preparation when cab, protection package or cab, protection package HD are not selected. CANNOT BE USED WITH: Tank, fuel fast fill & refill ready		\$1,195

OTHER ATTACHMENTS

COUNTERWEIGHT OPTIONS

P	340-5433	COUNTERWEIGHT, REAR SLAB 172 0 Additional weight 78kg / 172 lbs per slab. Slabs can be ordered quantity 1 or 2, INSTALLED with the machine, or through MISCELLANEOUS order. REQUIRES: Counterweight, rear		\$433 \$433 NI
---	----------	--	--	---------------------------------

MAINTENANCE AND RELATED ATTACHMENTS

L	460-1189	SHOVEL FASTENER 0 Convenient feature to fasten the shovel on the machine.		\$160
P	432-8643	FUEL PUMP, REFILLING 0 0 Provides an electrical fuel refilling pump (50 liters/min), with automatic shut-off. Refills the fuel tank in about 6 min. Includes 3 meter hose and filter. REQUIRES: fast fill and refill ready CANNOT BE USED WITH: Winch preparation		\$1,330 \$1,330 NI
L	431-4119	OIL CHANGE SYSTEM, HIGH SPEED 0 Easy access drain line and Wiggins connector for remote engine oil drain. Provides quick, clean and easy engine oil change without having to climb under the machine to access a gravity drain.		\$293

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT PO ENTRY
-----	---------	----------------------	-----------------	------------------------

FLUIDS

	0G-6009	ANTIFREEZE, -50C (-58F) 117 Provides cooling system antifreeze protection down to -50C		\$243 NET
--	----------------	--	--	------------------

FIELD INSTALLED ATTACHMENTS

AVAILABLE FROM PARTS DISTRIBUTION

PLEASE CONTACT PARTS DISTRIBUTION FOR CURRENT PRICES. ARRANGEMENTS MAY NOT BE AVAILABLE AS KITS, SO MAY REQUIRE ORDERING SEPARATE PARTS.

WINCH & FAIRLEAD

AVAILABLE THROUGH MISCELLANEOUS ORDERS FOR NACD AND LACD TERRITORIES.
Winches are shipped from the Parts Distribution System.
Orders must be placed via ANTARES.
AVAILABLE THROUGH PARTS DISTRIBUTION FOR EAME TERRITORY.

438-1061 PA50 WINCH, VARIABLE SPEED
Variable speed, hydrostatic winch.
Bare drum line pull: 50,000lbs
REQUIRES: Winch Preparation

187-1710 FAIRLEAD, 3 ROLLERS
ONLY FOR USE WITH: PA50 Winch

187-1713 KIT, CONVERSION, 4TH ROLLER
REQUIRES: Fairlead, 3 Rollers

373-8042 WINCH STEP

PACKING

EXPORT PACKING

	0G-3256	PACK-DISMOUNTED OR N.I. BLADE 0 Packing for a dismantled or not installed blade.		\$205 NET
	0G-3257	PACK-NOT INSTALLED RIPPER 0 Packing for a dismantled or not installed ripper.		\$253 NET
	0G-0370	PACK - SPECIAL MISC. MATERIAL 0 Packing for a dismantled or not installed attachment, out of the blades and rippers.		\$101 NET