

**Sector D - Storm Water Discharges Associated With Industrial Activity From Asphalt Paving and Roofing Materials and Lubricant Manufacturers**

**1. Discharges Covered Under This Section**

The requirements listed under this section shall apply to storm water discharges associated with industrial activity from a facility engaged in manufacturing the following products and generally described by the SIC codes shown below:

<b>SIC Code</b>	<b>Sector D: Asphalt Paving, Roofing Materials, and Lubricant Manufacturing Facilities</b>	<b>Sampling Required?</b>	<b>Table Number</b>
2951	Asphalt Paving Mixtures and Blocks	Yes	D-1 & 2
2952	Asphalt Felts and Coatings	Yes	D-1 & 2
2992	Lubricating Oils and Greases	No	

When an industrial facility, described by the above coverage provisions of this section, has industrial activities being conducted onsite that meet the description(s) of industrial activities in another section(s), that industrial facility shall comply with any and all applicable monitoring and pollution prevention plan requirements of the other section(s) in addition to all applicable requirements in this section. The monitoring and pollution prevention plan terms and conditions of this multi-sector permit are additive for industrial activities being conducted at the same industrial facility (co-located industrial activities). The operator of the facility shall determine which other monitoring and pollution prevention plan section(s) of this permit (if any) are applicable to the facility.

Limitations on Coverage. The following storm water discharges associated with industrial activity are not authorized by this section of the permit:

- Storm water discharges from petroleum refining facilities, including those that manufacture asphalt or asphalt products and that are classified as SIC code 2911,
- Storm water discharges from oil recycling facilities, and
- Storm water discharges associated with fats and oils rendering.

**2. Special Conditions**

Prohibition of Non-storm Water Discharges. Except for those allowable non-storm water discharges included in Part 3.1.2 (Allowable Non-Storm Water Discharges) of this permit, there are no other non-storm water discharges authorized in this Sector.

**3. Storm Water Pollution Prevention Plan Requirements**

3.1 Deadlines for Plan Preparation and Compliance. There are no additional deadlines for plan preparation and compliance, other than those stated in Part 4.1.

3.2 The plan shall include, at a minimum, the following items:

3.2.1 Pollution Prevention Team. Each plan shall identify a specific individual or individuals within the facility organization as members of a storm water Pollution Prevention Team that are responsible for developing the storm water pollution prevention plan and assisting the

**Sector D**

facility or plant manager in its implementation, maintenance, and revision. The plan shall clearly identify the responsibilities of each team member. The activities and responsibilities of the team shall address all aspects of the facility's storm water pollution prevention plan.

3.2.2 Description of Potential Pollutant Sources. Each plan shall provide a description of potential sources that may reasonably be expected to add significant amounts of pollutants to storm water discharges or that may result in the discharge of pollutants during dry weather from separate storm sewers draining the facility. Each plan shall identify all activities and significant materials that may potentially be significant pollutant sources. Each plan shall include, at a minimum:

3.2.2.1 Drainage. A site map indicating an outline of the portions of the drainage area of each storm water outfall that are within the facility boundaries, each existing structural control measure to reduce pollutants in storm water runoff, surface water bodies, locations where significant materials are exposed to precipitation, locations where major spills or leaks identified under 11.D.3.2.2.3 (spills and leaks) of this permit have occurred, and the locations of the following activities where such activities are exposed to precipitation: fueling stations, vehicle and equipment maintenance and/or cleaning areas, loading/unloading areas, locations used for the treatment, storage or disposal of wastes, liquid storage tanks, processing areas and storage areas including areas where raw materials, finished products and drums are stored. The map must indicate the outfall locations and the types of discharges contained in the drainage areas of the outfalls.

For each area of the facility that generates storm water discharges associated with industrial activity with a reasonable potential for containing significant amounts of pollutants, a prediction of the direction of flow, and an identification of the types of pollutants that are likely to be present in storm water discharges associated with industrial activity. Factors to consider include the toxicity of a chemical; quantity of chemicals used, produced or discharged; the likelihood of contact with storm water; and history of significant leaks or spills of toxic or hazardous pollutants. Flows with a significant potential for causing erosion shall be identified.

3.2.2.2 Inventory of Exposed Materials—An inventory of the types of materials handled at the site that potentially may be exposed to precipitation. Such inventory shall include a narrative description of significant materials that have been handled, treated, stored or disposed in a manner to allow exposure to storm water between the time of 3 years prior to the date of the submission of a Notice of Intent (NOI) to be covered under this permit and the present; method and location of onsite storage or disposal; materials management practices employed to minimize contact of materials with storm water runoff between the time of 3 years prior to the date of the submission of a Notice of Intent (NOI) to be covered under this permit and the present; the location and a description of existing structural and nonstructural control measures to reduce pollutants in storm water runoff; and a description of any treatment the storm water receives.

3.2.2.3 Spills and Leaks—A list of significant spills and significant leaks of toxic or hazardous pollutants that occurred at areas that are exposed to precipitation or that otherwise drain to a storm water conveyance at the facility after the date of 3 years prior to the date of the

**Sector D**

submission of a Notice of Intent (NOI) to be covered under this permit. Such list shall be updated as appropriate during the term of the permit.

- 3.2.2.4 Sampling Data—A summary of existing discharge sampling data describing pollutants in storm water discharges from the facility, including a summary of sampling data collected during the term of this permit.
- 3.2.2.5 Risk Identification and Summary of Potential Pollutant Sources—A narrative description of the potential pollutant sources from the following activities: loading and unloading operations; outdoor storage activities; outdoor manufacturing or processing activities; significant dust or particulate generating processes; and onsite waste disposal practices. The description shall specifically list any significant potential source of pollutants at the site and for each potential source, any pollutant or pollutant parameter (e.g., biochemical oxygen demand, etc.) of concern shall be identified.
- 3.2.3 Measures and Controls. Each facility covered by this permit shall develop a description of storm water management controls appropriate for the facility, and implement such controls. The appropriateness and priorities of controls in a plan shall reflect identified potential sources of pollutants at the facility. The description of storm water management controls shall address the following minimum components, including a schedule for implementing such controls:
- 3.2.3.1 Good Housekeeping—Good housekeeping requires the maintenance of areas that may contribute pollutants to storm water discharges in a clean, orderly manner. Particular attention should be paid to areas where raw materials are stockpiled, material handling areas, storage areas, liquid storage tanks, material handling areas, and loading/unloading areas.
- 3.2.3.2 Preventive Maintenance—A preventive maintenance program shall involve timely inspection and maintenance of storm water management devices (e.g., cleaning oil/water separators, catch basins) as well as inspecting and testing facility equipment and systems to uncover conditions that could cause breakdowns or failures resulting in discharges of pollutants to surface waters, and ensuring appropriate maintenance of such equipment and systems.
- 3.2.3.3 Spill Prevention and Response Procedures—Areas where potential spills that can contribute pollutants to storm water discharges can occur, and their accompanying drainage points shall be identified clearly in the storm water pollution prevention plan. Where appropriate, specifying material handling procedures, storage requirements, and use of equipment such as diversion valves in the plan should be considered. Procedures for cleaning up spills shall be identified in the plan and made available to the appropriate personnel. The necessary equipment to implement a clean up should be available to personnel.
- 3.2.3.4 Inspections—In addition to or as part of the comprehensive site evaluation required under this section, qualified facility personnel shall be identified to inspect designated equipment and areas of the facility at appropriate intervals specified in the plan. Material storage and handling areas, liquid storage tanks, hoppers or silos, vehicle and equipment maintenance, cleaning, and fueling areas, material handling vehicles, equipment and processing areas shall be inspected at least once per month as part of the maintenance program. A set of tracking or

Tennessee Storm Water Multi-Sector  
General Permit for Industrial Activities (TMSP)  
**Sector D**

follow-up procedures shall be used to ensure that appropriate actions are taken in response to the inspections. Records of inspections shall be maintained.

- 3.2.3.5 Employee Training—Employee training programs shall inform personnel responsible for implementing activities identified in the storm water pollution prevention plan or otherwise responsible for storm water management at all levels of responsibility of the components and goals of the storm water pollution prevention plan. Training should address topics such as spill response, good housekeeping and material management practices. The pollution prevention plan shall identify periodic dates for such training.
- 3.2.3.6 Recordkeeping and Internal Reporting Procedures—A description of incidents (such as spills, or other discharges), along with other information describing the quality and quantity of storm water discharges shall be included in the plan required under this part. Inspections and maintenance activities shall be documented and records of such activities shall be incorporated into the plan.
- 3.2.3.7 Non-storm Water Discharges
- 3.2.3.7.1 The plan shall include a certification that the discharge has been tested or evaluated for the presence of non-storm water discharges. The certification shall include the identification of potential significant sources of non-storm water at the site, a description of the results of any test and/or evaluation for the presence of non-storm water discharges, the evaluation criteria or testing method used, the date of any testing and/or evaluation, and the onsite drainage points that were directly observed during the test. Certifications shall be signed in accordance with Part 7.7 of this permit. Such certification may not be feasible if the facility operating the storm water discharge associated with industrial activity does not have access to an outfall, manhole, or other point of access to the ultimate conduit that receives the discharge. In such cases, the source identification section of the storm water pollution prevention plan shall indicate why the certification required by this part was not feasible, along with the identification of potential significant sources of non-storm water at the site. A discharger that is unable to provide the certification required by this paragraph must notify the Division of Water Pollution Control in accordance with paragraph “Failure to Certify” (below).
- 3.2.3.7.2 Sources of non-storm water that are combined with storm water discharges associated with industrial activity must be identified in the plan. The plan shall identify and ensure the implementation of appropriate pollution prevention measures for the non-storm water component(s) of the discharge. Any non-storm water discharges that are not authorized under this permit or another NPDES permit should be brought to the attention of the division’s local Environmental Field Office (see list of EFOs on page 14).
- 3.2.3.7.3 Failure to Certify—Any facility that is unable to provide the certification required (testing for non-storm water discharges), must notify the Division of Water Pollution Control not later than 180 days after submitting an NOI to be covered by this permit. If the failure to certify is caused by the inability to perform adequate tests or evaluations, such notification shall describe: the procedure of any test conducted for the presence of non-storm water discharges; the results of such test or other relevant observations; potential sources of non-storm water discharges to the storm sewer; and why adequate tests for such storm sewers

Tennessee Storm Water Multi-Sector  
General Permit for Industrial Activities (TMSP)  
**Sector D**

were not feasible. Non-storm water discharges to waters of the State that are not authorized by an NPDES permit are unlawful, and must be terminated.

- 3.2.3.8 Sediment and Erosion Control—The plan shall identify areas that, due to topography, activities, or other factors, have a high potential for significant soil erosion, and identify structural, vegetative, and/or stabilization measures to be used to limit erosion.
- 3.2.3.9 Management of Runoff—The plan shall contain a narrative consideration of the appropriateness of traditional storm water management practices (practices other than those that control the generation or source(s) of pollutants) used to divert, infiltrate, reuse, or otherwise manage storm water runoff in a manner that reduces pollutants in storm water discharges from the site. The plan shall provide that measures that the permittee determines to be reasonable and appropriate shall be implemented and maintained. The potential of various sources at the facility to contribute pollutants to storm water discharges associated with industrial activity [see paragraph D.3.2.2 of this section (Description of Potential Pollutant Sources)] shall be considered when determining reasonable and appropriate measures. Appropriate measures may include: vegetated swales, reuse of collected storm water (such as for a process or as an irrigation source), inlet controls (such as oil/water separators), infiltration devices, and detention/retention basins or other equivalent measures.
- 3.2.4 Comprehensive Site Compliance Evaluation. Qualified personnel shall conduct site compliance evaluations at appropriate intervals specified in the plan, but in no case less than once a year. Evaluations shall be conducted at least once at portable plant locations that are not in operation for a complete year. Such evaluations shall provide:
- 3.2.4.1 Areas contributing to a storm water discharge associated with industrial activity including; material storage and handling areas, liquid storage tanks, hoppers or silos, vehicle and equipment maintenance, cleaning, and fueling areas, material handling vehicles, equipment and processing areas, and areas where aggregate is stockpiled outdoors shall be visually inspected for evidence of, or the potential for, pollutants entering the drainage system. Measures to reduce pollutant loadings shall be evaluated to determine whether they are adequate and properly implemented in accordance with the terms of the permit or whether additional control measures are needed. Structural storm water management measures, (e.g., oil/water separators, detention ponds, sedimentation basins or equivalent measures) sediment and erosion control measures, and other structural pollution prevention measures identified in the plan shall be observed to ensure that they are operating correctly. A visual inspection of equipment needed to implement the plan, such as dust collection equipment and spill response equipment, shall be made.
- 3.2.4.2 Based on the results of the evaluation, the description of potential pollutant sources identified in the plan in accordance with D.3.2.2 of this section (description of potential pollutant sources) and pollution prevention measures and controls identified in the plan in accordance with 11.D.3.2.3 of this section (measures and controls) shall be revised as appropriate within 2 weeks of such evaluation and shall provide for implementation of any changes to the plan in a timely manner, but in no case later than 12 weeks after the evaluation.
- 3.2.4.3. A report summarizing the scope of the evaluation, personnel making the evaluation, the date(s) of the evaluation, major observations relating to the implementation of the storm

Tennessee Storm Water Multi-Sector  
 General Permit for Industrial Activities (TMSP)  
**Sector D**

water pollution prevention plan, and actions taken in accordance with paragraph D.3.2.3.2 (above) of the permit shall be made and retained as part of the storm water pollution prevention plan for at least 3 years after the date of the evaluation. The report shall identify any incidents of noncompliance. Where a report does not identify any incidents of noncompliance, the report shall contain a certification that the facility is in compliance with the storm water pollution prevention plan and this permit. The report shall be signed in accordance with Part 7.7 (Signatory Requirements) of this permit.

3.2.4.4 Where compliance evaluation schedules overlap with inspections required under D.3.2.3.4, the compliance evaluation may be conducted in place of one such inspection.

**4. Numeric Effluent Limitations.**

In addition to the numeric effluent limitations listed in Part 5.2 of this permit, discharges from areas where production of asphalt paving and roofing emulsions occurs may not exceed the following numeric limits.

**Table D-1. Numeric Effluent Limits for Asphalt Paving and Roofing Materials Mfg. Facilities**

<b>Pollutants of Concern</b>	<b>Daily Maximum</b>	<b>30-day Average</b>
Total Suspended Solids (TSS)	23 mg/L	15 mg/L
Oil and Grease	15 mg/L	10 mg/L
pH	6.0-9.0 standard units	

**5. Monitoring and Reporting Requirements**

One (1) signed copy of the Discharge Monitoring Report, DMR, (see Addendum D) for numeric effluent limits results or Annual Storm Water Monitoring Report (see Addendum E) for the benchmark results is required to be submitted to the division.

**5.1 Analytical Monitoring Requirements**

During the term of this permit, permittees covered under this sector must monitor their storm water discharges associated with industrial activity at least once per calendar year (annually), except as provided in paragraphs 5.1.3 (Sampling Waiver), 5.1.4 (Representative Discharge), and 5.1.5 (Alternative Certification). For SIC-specific breakdown of monitoring requirements and applicable Monitoring Requirements (listed below), see Table in Part 1 of this industrial sector (1. Discharges Covered Under This Section). Facilities must report in accordance with 5.2 (Reporting). In addition to the parameters listed in Table D-1 below, the permittee shall maintain a record of the date and duration (in hours) of the storm event(s) sampled; rainfall measurements or estimates (in inches) of the storm event that generated the sampled runoff; the duration between the storm event sampled and the end of the previous measurable (greater than 0.1 inch rainfall) storm event; and an estimate of the total volume (in gallons) of the discharge sampled.

Tennessee Storm Water Multi-Sector  
 General Permit for Industrial Activities (TMSP)  
**Sector D**

**Table D-2. Benchmark for Asphalt Paving and Roofing Materials Mfg. Facilities**

<b>Pollutants of Concern</b>	<b>Benchmark [mg/L]</b>	<b>Sector Median Value * [mg/L]</b>
Total Suspended Solids	150	24

\* Sector Median Value is a pollutant concentration calculated from all sampling results provided from facilities classified in this sector during the previous permit term. By definition, a median is a statistical term identifying a number that divides numerically ordered data into two equal halves. In easier terms, the median is the middle piece of data when those data are placed in numerical order, or the average of the middle two if there is an even number of items. Therefore, median concentration(s) listed above represent a concentration value typical for and achieved by industries in this sector.

5.1.1 **Monitoring Periods.** Asphalt paving and roofing materials manufacturing facilities shall monitor samples collected during any period of a calendar year, as long as the samples are representative of the quantity and quality of the storm water runoff being discharged from the facility.

5.1.2 **Sample Type.** A minimum of one grab sample shall be taken. All such samples shall be collected from the discharge resulting from a storm event that is greater than 0.1 inches in magnitude and that occurs at least 72 hours from the previously measurable (greater than 0.1 inch rainfall) storm event. The required 72-hour storm event interval is waived where the preceding measurable storm event did not result in a measurable discharge from the facility. The required 72-hour storm event interval may also be waived where the permittee documents that less than a 72-hour interval is representative for local storm events during the season when sampling is being conducted. The grab sample shall be taken during the first 30 minutes of the discharge. If the collection of a grab sample during the first 30 minutes is impracticable, a grab sample can be taken during the first hour of the discharge, and the discharger shall submit with the monitoring report a description of why a grab sample during the first 30 minutes was impracticable. If storm water discharges associated with industrial activity commingle with process or nonprocess water, then where practicable permittees must attempt to sample the storm water discharge before it mixes with the non-storm water discharge.

In addition, the permittee shall evaluate the results obtained from sampling and monitoring following the required annual sampling events to determine whether the facility is below, meets, or exceeds the monitoring benchmarks as shown in the table above. If the results of annual storm water runoff monitoring demonstrate that the facility has exceeded the benchmark(s), the permittee must inform the division’s local Environmental Field Office in writing within 30 days from the time storm water monitoring results were received, describing the likely cause of the exceedance(s). Furthermore, within 60 days from the time storm water monitoring results were received, the facility must review its storm water pollution prevention plan, make any modifications or additions to the plan which would assist in reducing effluent concentrations to less than the monitoring benchmarks for that facility, and submit to the division’s local Environmental Field Office a brief summary of the proposed SWPPP modifications (including a timetable for implementation).

5.1.3 **Sampling Waiver**

**Sector D**

- 5.1.3.1 Adverse Conditions—When a discharger is unable to collect samples within a specified sampling period due to adverse climatic conditions, the discharger shall collect a substitute sample from a separate qualifying event in the next period and submit the data along with data for the routine sample in that period. Adverse weather conditions that may prohibit the collection of samples include weather conditions that create dangerous conditions for personnel (such as local flooding, high winds, hurricanes, tornadoes, electrical storms, etc.) or otherwise make the collection of a sample impracticable (drought, extended frozen conditions, etc.).
- 5.1.3.2 Low Concentration Waiver—When the average concentration for a pollutant calculated from monitoring data collected from first 4 calendar years of monitoring is less than the corresponding reporting value for that pollutant (Monitoring Benchmark); a facility may waive monitoring and reporting requirements in the last annual monitoring period. The facility must submit to the Division of Water Pollution Control, in lieu of the monitoring data, a certification that there has not been a significant change in industrial activity or the pollution prevention measures in area of the facility that drains to the outfall for which sampling was waived.
- 5.1.3.3 When a discharger is unable to conduct annual chemical storm water sampling at an inactive and unstaffed site, the operator of the facility may exercise a waiver of the monitoring requirements as long as the facility remains inactive and unstaffed. The facility must submit to the Division of Water Pollution Control, in lieu of monitoring data, a certification statement on the TMSP Storm Water Monitoring Report stating that the site is inactive and unstaffed so that collecting a sample during a qualifying event is not possible.
- 5.1.3.4 Representative Discharge. When a facility has two or more outfalls that, based on a consideration of industrial activity, significant materials, and management practices and activities within the area drained by the outfall, the permittee reasonably believes discharge substantially identical effluents, the permittee may test the effluent of one of such outfalls and report that the quantitative data also applies to the substantially identical outfall(s) provided that the permittee includes in the storm water pollution prevention plan a description of the location of the outfalls and explains in detail why the outfalls are expected to discharge substantially identical effluents. In addition, for each outfall that the permittee believes is representative, an estimate of the size of the drainage area (in square feet) and an estimate of the runoff coefficient of the drainage area [e.g., low (under 40 percent), medium (40 to 65 percent), or high (above 65 percent)] shall be provided in the plan. The permittee shall include the description of the location of the outfalls, explanation of why outfalls are expected to discharge substantially identical effluents, and estimate of the size of the drainage area and runoff coefficient with the TMSP Storm Water Monitoring Report.
- 5.1.3.5 Alternative Certification. A discharger is not subject to the monitoring requirements of this section provided the discharger makes a certification for a given outfall or on a pollutant-by-pollutant basis in lieu of monitoring reports required under paragraph (b) below, under penalty of law, signed in accordance with Part 7.7 (Signatory Requirements), that material handling equipment or activities, raw materials, intermediate products, final products, waste materials, by-products, industrial machinery or operations, or significant materials from past industrial activity that are located in areas of the facility within the drainage area of the outfall are not presently exposed to storm water and are not expected to be exposed to storm

Tennessee Storm Water Multi-Sector  
General Permit for Industrial Activities (TMSP)  
**Sector D**

water for the certification period. Such certification must be retained in the storm water pollution prevention plan, and submitted to the Division of Water Pollution Control in accordance with Part 6.2. of this permit. In the case of certifying that a pollutant is not present, the permittee must submit the certification along with the monitoring reports required under paragraph (b) below. If the permittee cannot certify for an entire period, they must submit the date exposure was eliminated and any monitoring required up until that date. This certification option is not applicable to compliance monitoring requirements in part of this permit associated with effluent limitations.

5.2 Reporting

Permittees with analytical monitoring requirements shall submit monitoring results for each outfall associated with industrial activity [or a certification in accordance with Sections (3), (4), or (5) above] obtained during the annual reporting period on TMSP Storm Water Monitoring Report Form(s) postmarked no later than the March 31st of the following calendar year. For each outfall, one signed TMSP Storm Water Monitoring Report form must be submitted to the Division of Water Pollution Control. Signed copies of TMSP Storm Water Monitoring Reports, or said certifications, shall be submitted to the division at the appropriate EFO for the county where the facility is located. A list of EFOs and their addresses are available in subpart 3.3 above.

5.3 Quarterly Visual Examination of Storm Water Quality. Facilities shall perform and document a visual examination of a storm water discharge associated with industrial activity from each outfall, except discharges exempted below. The examination must be made at least once in each designated period [described in (5.3.1), below] during daylight hours unless there is insufficient rainfall or snow melt to produce a runoff event.

5.3.1 Examinations shall be conducted in each of the following periods for the purposes of evaluating storm water quality associated with storm water runoff or snow melt: January through March; April through June; July through September; and October through December.

5.3.2 Examinations shall be made of samples collected within the first 30 minutes (or as soon thereafter as practical, but not to exceed 1 hour) of when the runoff or snowmelt begins discharging. The examinations shall document observations of color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and other obvious indicators of storm water pollution. The examination must be conducted in a well lit area. No analytical tests are required to be performed on the samples. All such samples shall be collected from the discharge resulting from a storm event that is greater than 0.1 inches in magnitude and that occurs at least 72 hours from the previously measurable (greater than 0.1 inch rainfall) storm event. Where practicable, the same individual should carry out the collection and examination of discharges for the life of the permit.

**Sector D**

- 5.3.3 Visual examination reports must be maintained onsite in the pollution prevention plan or with other compliance records. The report shall include the examination date and time, examination personnel, the nature of the discharge (i.e., runoff or snow melt), visual quality of the storm water discharge (including observations of color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and other obvious indicators of storm water pollution), and probable sources of any observed storm water contamination.
- 5.3.4 When a facility has two or more outfalls that, based on a consideration of industrial activity, significant materials, and management practices and activities within the area drained by the outfall, the permittee reasonably believes discharge substantially identical effluents, the permittee may collect a sample of effluent of one of such outfalls and report that the examination data also applies to the substantially identical outfalls provided that the permittee includes in the storm water pollution prevention plan a description of the location of the outfalls and explaining in detail why the outfalls are expected to discharge substantially identical effluents. In addition, for each outfall that the permittee believes is representative, an estimate of the size of the drainage area (in square feet) and an estimate of the runoff coefficient of the drainage area [e.g., low (under 40 percent), medium (40 to 65 percent), or high (above 65 percent)] shall be provided in the plan.
- 5.3.5 When a discharger is unable to collect samples over the course of the visual examination period as a result of adverse climatic conditions, the discharger must document the reason for not performing the visual examination and retain this documentation on site with the results of the visual examination. Adverse weather conditions that may prohibit the collection of samples include weather conditions that create dangerous conditions for personnel (such as local flooding, high winds, hurricanes, tornadoes, electrical storms, etc.) or otherwise make the collection of a sample impracticable (drought, extended frozen conditions, etc.).
- 5.3.6 When a discharger is unable to conduct visual storm water examinations at an inactive and unstaffed site, the operator of the facility may exercise a waiver of the monitoring requirement as long as the facility remains inactive and unstaffed. The facility must maintain a certification with the pollution prevention plan stating that the site is inactive and unstaffed so that performing visual examinations during a qualifying event is not feasible.
- 5.4 Compliance Monitoring Requirements. Permittees with facilities that produce asphalt paving or roofing emulsions must monitor their storm water discharges associated with these activities for the presence of TSS, oil and grease, and for pH at least annually (one time per year) according to 5.12. Facilities must report in accordance with 5.2 (Reporting). In addition to the parameters listed above, the permittee shall maintain a record of the date and duration (in hours) of the storm event(s) sampled; rainfall measurements or estimates (in inches) of the storm event that generated the sampled runoff; the duration between the storm event sampled and the end of the previous measurable (greater than 0.1 inch rainfall) storm event; and an estimate of the total volume (in gallons) of the discharge sampled.